	т (Ф. 1997) т (Т. 1997) т (T.				
4					4
ω			LAYOUT SHOWN AS EXAMPLE		3
	Keying Shown as example				
	CHARACTERISTICS Connector dimension				
	Dim Nominal -Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed			
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories		PN: 8D511W22PC		
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours	A 18-10-2016	First Release		
	-Mass : 14.47 g ± 10%	ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	<u>N°</u>
		TITLE	TITLE Aluminium Plug 8D series		
_	BASIC SERIES: 8D 5 - 11 W 22 P C SHELL TYPE : Plug with RFI Shielding	SCALE -	General linear Tolerances:	NPRDS / PROJECT 859	
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 CONTACT TYPE : PIN(500 Matings)		SOURIAU This document is the proper SOURIAU SOURIAU it must not be reproduced communicated without permit		
	PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 11-22		SOURIAU DRG		T
		A3	8D511W22P0	C-C 1/2	

	T	<u>م</u>	п П	m	D	0
4		Contact Layout 22*				
	Ctc A B C D	11-22 X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905 -1.905 1.905				
						SOURIAU shall not be liable for due to a use of the Products the Specifications issued by either (professional recomment
27						PN: 8D511
					A 18-10-201 ISS DATE Designed By:	6 First Release Latest modification - by Date:
-					TITLE SCALE NA	Alum General linear Tolerances: ±
					FORMAT	J WWW.SOURIAU SOURIA

G

Н

F

Е

A3

D

С

