

BASIC SERIES.		5 00	_		1 **	ſ						_ſ.	$-+(\oplus)$	
SHELL TYPE : Plug with	n RFI Shielding	g									NA		$\neg \Psi$	
CONTACT TYPE : Standard Crimp Contact						ORIENTATION :					WWW.S			
SHELL SIZE : 19							CONTACT TYPE : PIN(500 Matings)							
PLATING : K = F	Passivated								COI	NTACT LAYOUT : 19	9-11 FORMAT			
											A3			
Н		G				F			Е		D		С	

\_

			4						
	A.								
			3						
LAYOUT SHOWN AS EXAMPLE			-						
all not be liable for any non-conformity or damage									
use of the Products which does not comply with ons issued by either of the Parties or by a third party									
essional recommendation, technical notice.)									
CountryJurisdiction & Control ListFRNot Listed									
PN: 8D519K11PD									
ation - by		MOD N°							
te:	CUSTOMER DRAWING	NODN							
Stainless Steel Plug	8D series								
General linear Tolerances:	NPRDS / PROJECT								
± 859   This document is the property of									
<b>W.SOURIAU.COM</b> it must not be reproduced or									
communicated without permission									
SOURIAU DRG N°		SHEET 1/2							
8D519K11PD-C	A	1/2							
I D	I A								

ſ	Т	Q	וד	т		0	Ξ			,
		Contact Layout								
4										4
		$\overset{J}{\overset{J}{\textcircled{\baselineskip}{\baselineskip}}} \overset{J}{\overset{J}{\textcircled{\baselineskip}{\baselineskip}}} \overset{A}{\overset{A}{\textcircled{\baselineskip}{\baselineskip}}} \overset{A}{\overset{B}{\textcircled{\baselineskip}{\baselineskip}}} \overset{A}{\overset{B}{\r}} \overset{A}{\overset{B}{\r}} \overset{A}{\overset{B}{\r}} \overset{A}{\overset{B}} \overset{A}{\overset{B}}{\overset{B}} \overset{A}{\overset{B}} \overset{A} \overset{A}{\overset{B}} \overset{A}{\overset{B}} $								
		$ \begin{array}{cccc} & \oplus^{H} & \oplus^{K} & \oplus^{C} \\ & & + \\ & \oplus_{E} & \oplus^{C} & \oplus^{C} \\ & & & \oplus_{E} & \oplus_{E} \end{array}  \right)  \times $								
_		vy € SYM Contacts								
	Contact position ID (mm) A +.105 (2.67)	(Insert arrangement 19-11)       tion     Contract position     Location       Y-axis     position     X-axis     Y-axis       (mm)     ID     (mm)     (mm)								
	B + 250 (6.35) C + 275 (6.99) D + .179 (4.55) E +.000 (0.00) F179 (4.55)	+.132 (3.35)     H    250 (6.35)     +.132 (3.35)      053 (1.35)     J    105 (2.67)     +.260 (6.60)      215 (5.46)     K     +.000 (0.00)     +.105 (2.67)      281 (7.14)     L     +.000 (0.00)    092 (2.34)								
ω	Sheli Arrangement Nu size no. cc 19 -11	mber of Size Service Contact Supersedes ntacts contacts rating location 11 16 II All MS20054-11								3
	_									
	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with									
	the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)									
N						Country FR		on & Control List lot Listed		2
	PN: 8D519K11PD									
					A 18-10-2016	D-2016 First Release				
					ISS DATE	Latest modification - by			MOD N°	
			Designed By: Date: CUSTOMER DRAWING							
		TITLE Stainless Steel Plug 8D series								-
_					SCALE -	General linear Tolerances: ±		NPRDS / PROJECT <b>859</b>		1
					SOURIAU	WWW.SOURIAU.C	DM MC	This document is the pro SOURIAU it must not be reproduc		
					FORMAT			communicated without pe		
					A3	SOURIAU 8D519K1			2/2	
L	Н	G	F	E	D	С	В	А		