	יד (ד	D	0	₩	Þ	
	ØS					
			LAYOUT SHOWN AS	EXAMPLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension]				
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum	DimNominalØS25 MaxZ'31.5 MaxVV THREADM15x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed			
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D511M01BE			
-Temperature Range <u>-</u> -65°C to +200°C -Salt Spray : 2000 hours		A 16-10-2	2016 First Release			
-Salt Spray : 2000 hours Mass : 15.7 g ± 10%		ISS DAT Designed By:	E Latest modification - by Date:	CUSTON	MOD N IER DRAWING	
		TITLE	TITLE Composite Plug 8D series		5	
BASIC SERIES: 8D 5 - 11 M SHELL TYPE : Plug with RFI Shielding	01 B E	SCALE	General linear Tolerances:		S / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact ORIENTATION : E			SOURIAU This document is the property of SOURIAU it must not be reproduced or communicated without permission			
SHELL SIZE : 11	CONTACT TYPE : SOCKET(5	00 10 10 10 10 10 10 10 10 10 10 10 10 1				
	CONTACT TYPE : SOCKET(5			U DRG N° ⁄/01BE-C	SHEET	

	工	G	нт — — — — — — — — — — — — — — — — — — —	т	U	0
		Contact Layout				
4		01				
		1#12 11-01	٦			
ω	Ctc A	X Y 0 0				
	\vdash					SOURIAU shall not be liable for any due to a use of the Products wh
0						the Specifications issued by either of (professional recommendat Countr FR
					A 16-10-20 ISS DATE Designed By:	PN: 8D511N 16 First Release Latest modification - by Date:
_					TITLE SCALE NA	General linear Tolerances:
					SOURIA	U WWW.SOURIAU.C
	Н	G	F	E	FORMAT A3	SOURIAU 8D511M C
	П		I F			

