

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of GCM31C5C2J822GX03# from the official website of Murata Manufacturing Co., Ltd.

"#" indicates a package specification code.

http://www.murata.com/en-us/products/productdetail?partno=GCM31C5C2J822GX03%23

## GCM31C5C2J822GX03L



< List of part numbers with package codes > GCM31C5C2J822GX03L GCM31C5C2J822GX03K

### Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Automotive powertrain/safety equipment,
	Automotive infotainment/comfort
	equipment,Medical equipment [GHTF
	A/B/C] except for implant equipment
	Please refer to Our Website and
Specific	specifications, etc. for information about
Applications	the performance, functions, quality,
	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.


# References

	Specifications	Standard
Packaging		Packing
		Quantity
L	180Embossed Tape	2000
К	330Embossed Tape	8000

Mass (typ.)		
1 piece	38.0mg	

## Appearance & Shape





1 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





## GCM31C5C2J822GX03L

Note: This datasheet may be out of date. Please download the latest datasheet of GCM31C5C2J822GX03# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GCM31C5C2J822GX03%23

### "#" indicates a package specification code.



### Specifications

Length	3.2±0.2mm
Width	1.6±0.2mm
Thickness	1.6±0.2mm
Capacitance	8200pF ±2%
Distance between external terminals g	1.5mm min.
External terminal size e	0.3mm min.
Operating Temperature Range	-55℃ to 125℃
Rated Voltage	630Vdc
Size code in inch(mm)	1206 (3216M)
ТС	0±30ppm/°C
Temperature characteristics (complied standard)	C0G(EIA)
Temperature range of temperature characteristics	25℃ to 125℃

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

