This product is not orderable anymore. Contact your local distribution partner for alternatives.



# Han 24B-HTE-R-NPTF 1"

TIGHT 2-TO THE IX IN THE		
	Part number	09 30 524 0441
	Specification	Han 24B-HTE-R-NPTF 1"
	HARTING eCatalogue	https://b2b.harting.com/09305240441

## Identification

Category	Hoods/Housings
Series of hoods/housings	Han <sup>®</sup> B
Type of hood/housing	Hood
Туре	High construction

### Version

Size	24 B
Version	Top entry
Locking type	Single locking lever
Field of application	Standard hoods/housings for industrial connectors

## Technical characteristics

Limiting temperature	-40 +125 °C
	IP65
Degree of protection acc. to IEC 60529	IP66
	IP67

# Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	No

Page 1 / 2 | Creation date 2021-10-01 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany

Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

This product is not orderable anymore. Contact your local distribution partner for alternatives.



# Material properties

REACH ANNEX XIV substances	No
REACH SVHC substances	No

# Specifications and approvals

Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
CE	Yes

#### Commercial data

Packaging size	1
Net weight	244 g
Country of origin	China
eCl@ss	27440202 Shell for industrial connectors