HS LC-H-D3PL/ R1XC4 - Fiber optic



1474382

https://www.phoenixcontact.com/us/products/1474382

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Multiple light guides, passive, rigid, can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed)



Your advantages

- · Light guides are perfectly matched to electronics housings
- · Easy mounting on the PCB using press pins
- · Resistance to ESD
- · Housing processing available on request
- Enables simple visual status and diagnostic indicators

Commercial Data

| Item number | 1474382 |
|--------------------------------------|---------------|
| Packing unit | 1 pc |
| Minimum order quantity | 100 pc |
| Sales Key | AC05 |
| Product Key | ACGABA |
| GTIN | 4063151888619 |
| Weight per Piece (including packing) | 1.24 g |
| Weight per Piece (excluding packing) | 1.24 g |
| Customs tariff number | 90019000 |
| Country of origin | DE |

HS LC-H-D3PL/ R1XC4 - Fiber optic



1474382

https://www.phoenixcontact.com/us/products/1474382

Technical Data

Notes

| | Refer to the data sheet for the range in the download area. | | | | |
|--------------------|---|--|--|--|--|
| Product properties | | | | | |
| | Fiber optic | | | | |
| itions | 4 | | | | |
| | 5.08 mm | | | | |
| s | 1 | | | | |
| | Horizontal | | | | |
| | passive, rigid | | | | |
| 9 | Multiple light guides | | | | |
| | Cylinder head | | | | |
| | itions | | | | |

4 (1 row x 4 columns)

Electrical properties

Number of indicators

Dimensions

| Diameter | 2 mm |
|---------------|---------|
| Hole diameter | 2.3 mm |
| Pitch | 5.08 mm |

Material specifications

| Color | transparent |
|---------------------|-------------|
| Insulating material | PMMA |

Environmental and real-life conditions

Ambient conditions

| Max. IP code to attain | IP20 |
|---------------------------------|--------------|
| Ambient temperature (operation) | -40 °C 85 °C |

HS LC-H-D3PL/ R1XC4 - Fiber optic



1474382

https://www.phoenixcontact.com/us/products/1474382

Classifications

ECLASS

| | ECLASS-11.0 | 27182702 | | | |
|----|-------------|----------|--|--|--|
| Εī | ETIM | | | | |
| | ETIM 8.0 | EC001031 | | | |

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com