
NOTE: CONTACTS MUST BE PURCHASED SEPARATELY




MATERIAL:

SHELL: NICKEL OR TIN PLATED STEEL INSULATOR: UL94 V-0 RATED, PBT-BLACK (FRONT INSULATOR) UL94 V-0 RATED, PA66-BLACK (REAR INSULATOR) PROCESS TEMP: 230°C

ELECTRICAL:

CURRENT RATING: 5 AMPS CONTACT RESISTANCE: 15 mOhms Max. INSULATION RESISTANCE: 1,000 MOhms min. OPERATING TEMPERATURE: -50° C TO 100° C

VOLTAGE: 500VAC FOR 1 MINUTE



	+ ±0.010	•
61 [4.10]		0.035 [0.90] ±0.012
272 [6.90]		G
±0.010		±0.010

IS
LE
TION
IMP & POKE
ATING
I (DISCONTINUED)
CKEL (GROUND INDENTS)
RE OPTIONS
O HARDWARE
98" CLINCH NUT (SOLDER SIDE)
36" CLINCH NUT (SOLDER SIDE)
36" CLINCH NUT (MATING SIDE)
OPTIONS
CONTACTS

		DIMENSIONS						
No. OF PINS	UNITS	А	В	С	D	Е	F	G
9	inch	1.213	0.984	0.666	0.329	0.618	0.496	0.429
	mm	30.80	24.99	16.92	8.36	15.70	12.60	10.90
15	inch	1.541	1.312	0.994	0.329	0.933	0.496	0.429
	mm	39.15	33.32	25.25	8.36	23.70	12.60	10.90
25	inch	2.087	1.852	1.534	0.329	1.496	0.496	0.429
	mm	53.00	47.04	38.96	8.36	38.00	12.60	10.90
37	inch	2.728	2.500	2.182	0.329	2.142	0.496	0.429
	mm	69.30	63.50	55.42	8.36	54.40	12.60	10.90
50	inch	2.638	2.402	2.079	0.436	2.039	0.602	0.535
	mm	67.00	61.00	52.80	11.07	51.80	15.30	13.60

RoHS COMPLIANT



DRAWN: THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE DATE: BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

	UNITS = inch [m
VN:	
P. JENKINS	NorC
 08/18/1998	

m] DO	NOT SC/	ALE FROM	n draw	ING
	SCALE: NTS	SHEET OF	2	REV 17
omp	DWG NO. 170-YYY-17YLYY0			

