	т (Ф. 1997) т. т. т. (С. 1997) т. т. (С. 1997) т. т. (С. 1997) т. (С.				
4			4		
ယ		LAYOUT SHOWN AS EXAMPLE	3		
	Keying Shown as example				
	-Standard : Based on MIL-DTL-38999 Series III Dim Nominal				
	-Shell Material: AluminiumØS25 Max-Shell Plating: Olive drab CadmiumZ31 Max-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List	2		
N	-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories	FR Not Listed PN: 8D511W22PD			
	-Temperature Range65°C to +175°C	A 18-10-2016 First Release			
	-Salt Spray : 500 hours	ISS DATE Latest modification - by MO			
	-Mass : 14.47 g ± 10%	Designed By: Date: CUSTOMER DRAWING			
		TITLE Aluminium Plug 8D series			
_	BASIC SERIES: 8D 5 - 11 W 22 P D SHELL TYPE : Plug with RFI Shielding - - 11 W 22 P D	SCALE General linear NPRDS / PROJECT NA 859	1		
	CONTACT TYPE : Standard Crimp Contact ORIENTATION : D	- SOURIAU WWW.SOURIAU.COW it must not be reproduced or			
	SHELL SIZE : 11 CONTACT TYPE : PIN(500 Matings)	-	n HEET		
	PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 11-22		/2		
		A3 8D511W22PD-C 1/	-		

		<u>م</u>	н т	m		0	
4		Contact Layout 22*					
ω	Ctc A B C D	11-22 X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905 -1.905 1.905					
						SOURIAU shall not be lia due to a use of the Pr the Specifications issued b (professional reco	oducts w
N						PN: 80	Coun FR 0511
_					A 18-10-2016 ISS DATE Designed By:	5 First Release Latest modification - by Date:	
-					TITLE SCALE NA	Gene Tole	Alumi ral linear erances: ±
					FORMAT		JRIAU.

G

Н

F

Е

A3

D

С

