			0	₿ >	
Z ØS Image: state st					
			LAYOUT SHOWN AS EXAM	MPLE	
	Keying Shown as example				
CHARACTERISTICS	Connector dimension				
Standard : Based on MIL-DTL-38999 Series III	DimNominalØS29.4 Max				
-Shell Material : Aluminium	Z 31 Max		SOURIAU shall not be liable for any no		
-Shell Plating : Black Zinc Nickel	VV THREAD M18x1-6g	due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party			
-Insulator : Thermoplastic -Contacts : Copper Alloy			(professional recommendation		
-Seals & Grommet : Silicon Elastomer]
-Contact Plating : Gold over copper Alloy 0.8µm minimum			Country FR	Jurisdiction & Control List Not Listed	_
-Durability : 500 Mating cycles					
-Delivered without Souriau contacts			PN: 8D513Z04	4SAL	
-Temperature Range <u>-</u> -65°C to +175°C					
-Salt Spray : 500 hours		A 19-10-2016	5 First Release		
Mass : 21.7 g ± 10%		ISS DATE	Latest modification - by		MOD N°
		Designed By:	Date:	CUSTOMER DRAWING	
		TITLE	Aluminiu	m Plug 8D series	
BASIC SERIES: 8D 5 - 13 Z	04 S A L	SCALE	General linear	NPRDS / PROJECT	
SHELL TYPE : Plug with RFI Shielding	Delivered W/O Conta	acts NA	Tolerances:	859	
CONTACT TYPE : Standard Crimp Contact	ORIENTATION			This document is the provide the SOURIAU	operty of
	CONTACT TYPE : SOCKET(500 Matin	- SOURIAU	WWW.SOURIAU.CO	IVI it must not be reprodu	
	I INTACT INDE • SOCKET/SOO Matir	igs)		communicated without p	ermission
SHELL SIZE : 13					
	CONTACT TIPE : SOCKET(SOU Math	-04 FORMAT A3	SOURIAU D 8D513Z04		SHEET

	工	۵	г П	m		0
		Contact Layout				
4		$x \begin{pmatrix} & & & \\ & & $				
	Contine position A B C C C D D D C D C D C D D D D D D D D D D D D D	n ID (mm) (mm) +.000 (0.00) +.150 (3.81) +.146 (3.71) +.035 (0.89) +.000 (0.00) 083 (2.11) 146 (3.71) +.035 (0.89)				
ယ						
						SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda
2						Countr FR
						PN: 8D5132
						116 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumir
_					SCALE	General linear Tolerances:
					SOURIA	
					FORMAT	SOURIAU
					A3	8D513Z0
	Н	G	F F	E	D	C

σ				A		
						4
						3
any non-cor which does r of the Part dation, tech ntry	not com ies or by nical no	nply with v a third pa	arty			
R		Not Listed				2
3Z04SA					/OD N°	
		CUSTOM	ER DRAWIN			
inium Plug 8D series						
r	NPRDS / PROJECT					
			859	0.0000	of	1
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
					SHEET 2/2	
ZO4SAL	L				<i>41 4</i>	
В		I		А		