	т Q I	m		0	₩		
Image: state of the state							4
CHARACTERISTICS Standard: iBased on MIL-0TL-38999 Series III Schell Material :: Aluminium Schell Material :: Black Clan Nickel insulator : Sold ver copper Alloy 0.8µm minimum Orntact Plaing :: Gold ver copper Alloy 0.8µm minimum Orntact Plaing :: Gold ver copper Alloy 0.8µm minimum Orntact and Accessories : Delevered with Souriau contast and Accessories : Delevered with Souriau contast and Accessories : Self S proy ::::::::::::::::::::::::::::::::::::				LAYOUT SHOWN AS EX	XAMPLE		6
Standard: Based on MILDTL-38999 Series II Shell Material :: Advantation Shell Material :: Advantation Shell Material :: Advantation Shell Material :: Advantation - Shell Material :: Advantation - Shell Material :: Advantation - Shell Naterial :: Advantation - Shell Naterial :: Advantation - Contact Pating :: Gold over copper Alloy 0.8µm minimum - Seals & Grommet :: Slicon Elastomer - Ournability :: Sold Over copper Alloy 0.8µm minimum - Ournability :: Sold Over copper Alloy 0.8µm minimum - Ournability :: Sold Over copper Alloy 0.8µm minimum - Ournability :: Sold Over copper Alloy 0.8µm minimum - Ournability :: Sold Over copper Alloy 0.8µm minimum - Delivered with Souriau contacts and Accessories	Keying SI	hown as example					
Shell Material ::::::::::::::::::::::::::::::::::::							
- Delivered with Souriau contacts and Accessories - Temperature Range :: -65°C to +175°C - Salt Spray :: 500 hours - Salt	-Shell Material: Aluminium-Shell Plating: Black Zinc Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer	Z 31 Max	due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				2
-Salt Spray : 500 hours -Salt Spray : 500 hours A 07-10-2016 ISS DATE Latest modification - by BASIC SERIES: 8D SHELL TYPE Plug with RFI Shielding CONTACT TYPE Standard Crimp Contact SHELL SIZE 23 PLATING : Z = Black Zinc Nickel ORIENTATION : N CONTACT TYPE SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU.COM SOURIAU SOURIAU WWW.SOURIAU.COM FORMAT SOURIAU DRG N°			PN: 8D523Z06SN				
Image: standard Crimp Contact 23 Z 06 S N Image: standard Crimp Contact SCALE N CONTACT TYPE Standard Crimp Contact SSOURIAU SSOURIAU SSOURIAU SSOURIAU This document is the proproduced or communicated without permission PLATING : z Black Zinc Nickel CONTACT TYPE SOURIAU DRG N° SHELT SHELL SIZE : : CONTACT TYPE SOURIAU DRG N° SHEET			A 07-10-2016	First Release			
BASIC SERIES: 8D 5 - 23 Z 06 S N BASIC SERIES: 8D 5 - 23 Z 06 S N SHELL TYPE : Plug with RFI Shielding - 23 Z 06 S N ORIENTATION : N NA General linear Tolerances: ± NPRDS / PROJECT CONTACT TYPE : Standard Crimp Contact ORIENTATION : N NA WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 23-06 FORMAT SOURIAU DRG N° SHEET	-Salt Spray : 500 hours						N°
BASIC SERIES: 8D 5 - 23 Z 06 S N SCALE SCALE NA Tolerances: 859 SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact ORIENTATION : N NA SCALE NA 859 SHELL SIZE : 23 PLATING : CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) SOURIAU This document is the property of SOURIAU communicated without permission PLATING : Z = Black Zinc Nickel CONTACT TYPE : SOCKET(500 Matings) FORMAT SOURIAU DRG N° SHEET							
BASIC SERIES. BD SD SD <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>							
CONTACT TYPE : Standard Crimp Contact ORIENTATION : N SHELL SIZE : 23 CONTACT TYPE : SOCKET(500 Matings) PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 23-06 FORMAT SOURIAU This document is the property of SOURIAU.COM Black Zinc Nickel CONTACT LAYOUT : 23-06 FORMAT SOURIAU DRG N°		N	-	Tolerances:	NF		
PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 23-06 FORMAT SOURIAU DRG N° SHEET	CONTACT TYPE : Standard Crimp Contact		N SOURIAU SOURIAU WWW.SOURIAU.COM it must not be reproduced or				
			FORMAT				
A3 8D523Z06SN-C 1/2			A3				

ſ	т	۵	г	m	D	0
		Contact Layout				
		06				
4						
		(
		6#8 Concentric				
		Twinax Service M				
		23-06]			
	Ctc	X Y				
	A	0 9.24	-			
	B	8.81 2.87 5.43 -7.49	-			
ယ	D	-5.43 -7.49	-			
	E	-8.81 2.87				
	F	0 0				
	1					
$ \rightarrow $	-					SOURIAU shall not be liable for an
						due to a use of the Products w
						the Specifications issued by either o (professional recommenda
N						Count FR
						PN: 8D523
					A 07-10-20	16 First Release
					ISS DATE Designed By:	Latest modification - by Date:
						Date.
					TITLE	Alumir
					SCALE	General linear
→					NA	tolerances:
					SOURIA	U WWW.SOURIAU.C
					FORMAT	SOURIAU
					A3	8D523Z
l	Н	G	F	E	7 D	
					/	

