	G	П	m	τ	7	C		Ξ	A		_
22.6 Mi						<image/>	YOUT SHOWN AS EXAM	MPLE			4
CHARACTERISTICS -Standard : Based on MIL-DTL-3	8999 Series III	Keying Shown as	Connector dimension Dim Nominal	]							
-Insulator : Therr -Contacts : Copp	Zinc Nickel oplastic		A     38.1±0.3       B     23.82+0.1/-0.15       R     32.5Max       S     34.9±0.4       W     2.2+0.9/-0.1       VV THREAD     M18x1-6g			due to a use the Specification	not be liable for any no e of the Products which is issued by either of the sional recommendation	does not comply e Parties or by a th , technical notice.	with hird party )		
► -Contact Plating : Gold	over copper Alloy 0.8µm minimum lating cycles	1				l	Country FR PN: 8D713Z0	Not	n & Control List t Listed		2
	-Temperature Range : -65°C to +175°C									-	
	g ± 10%				ISS DATE Designed By:	E Latest modificati Date:		CUS	STOMER DRAWING	MOD N°	
	Aluminium Receptacle 8D series										
BASIC SERIES: SHELL TYPE : Jam nut Recepta		Z 08 P D			SCALE NA		General linear Tolerances: ±		NPRDS / PROJECT 859		1
CONTACT TYPE : Standard Cr SHELL SIZE : 13	mp Contact		ORIEN CONTACT TYPE : PIN(50	ITATION : D 00 Matings)	SOURIA	U www	.Souriau.co	M	This document is the pro SOURIAU it must not be reprodu communicated without po	ced or	
PLATING : Z = Black Zir	Nickel		CONTACT LAYC	OUT : 13-08	format A3		SOURIAU D 8D713Z08			SHEET	
Н	G	F	E		D	C		В	A		

ſ	Т	G	нт.	т	D	O	Φ	A	
4		Contact Layout $x \xrightarrow{G \oplus \Phi^{A}} \oplus \oplus^{H} \oplus_{B} + x$ $x \xrightarrow{F \oplus \Phi^{C}} \oplus \oplus^{C} \oplus_{L} \oplus$				Panel cutout JAM NUT RECEPTACLE (TYPE 7)	∧ ∞		4
		X-axis (mm)         Y-axis (mm)           A         +.065 (1.65)         +.157 (3.99)           B         +.170 (4.32)         +.000 (0.00)           C         +.120 (3.05)        120 (3.05)           D         ·.000 (0.00)        170 (4.32)           E        120 (3.05)        120 (3.05)           F        170 (4.32)         +.000 (0.00)           G        065 (1.65)         +.157 (3.99)           H         +.000 (0.00)         +.044 (1.12)	7			Dim Nominal	V		
ω		Imber of ontacts     Size contacts     Service rating     Contact location     Supersedes       8     20     I     All     MS20051-8				B 24.26+0/-0.2 ØC 25.65+0.25/-			3
	_	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)							
23						PN: 8D	Country Jurisdi FR 713Z08PD	ction & Control List Not Listed	2
					A 29-09-2016 ISS DATE Designed By: TITLE	5 First Release Latest modification - by Date: Alum	inium Receptacl	CUSTOMER DRAWING e 8D series	<u>N°</u>
<b>_</b>					SCALE NA SOURIAU	General Tolerar ±	nces: -	NPRDS / PROJECT <b>859</b> This document is the property of SOURIAU it must not be reproduced or communicated without permission	1
	Н	G	F	E	FORMAT A3 D		RIAU DRG N° 13Z08PD-C B	communicated without permission SHEE 2/2 A	