ſ	т	۵		П	п				C		
4		R Max W O O O O O O O O O O O O O O O O O O	VV Thread			ØA					
	Keying Shown as example										
N	CHARACTERISTICS -Standard : Based on MIL-D -Shell Material : St -Shell Plating : Ni -Insulator : Th -Contacts : Co -Seals & Grommet : Sil -Contact Plating : Go -Durability : 50	n minimum		Connector dim Dim 4 A 42 B 42 R 5 W 42 VV THREAD 1		SOURIAU sh due to a u the Specificati (profe					
		tacts and Accessories 55°C to +200°C 00 hours					ISS Designe	DATE	First Release Latest modificat Date		
-	BASIC SERIES: SHELL TYPE : Jam nut Rece CONTACT TYPE : Standard SHELL SIZE : 25		25 S 6	1   B   C	CONTACT TY	ORIENTAT /PE : SOCKET(500 N	SCA N/ FION : C <b>SO</b>	LE	www.		
	PLATING : S = Nicke	<u>ا</u>				CONTACT LAYOUT	: 25-61 FORM				
								3			
	Н	G		F	l E	$\backslash \uparrow /$	D		С		

	Β			A			
						4	
LAYOUT SHOWN AS EXA	MPLE					3	
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) <u>Country</u> Jurisdiction & Control List FR Not Listed PN: 8D725S61BC							
ation - by MOD N° te: CUSTOMER DRAWING Stainless Steel Receptacle 8D series							
General linear NPRDS / PROJECT   Tolerances: 859   ± This document is the property of						1	
SOURIAU.COM   SOURIAU it must not be reproduced or communicated without permission     SOURIAU DRG N°   SHEET     8D725S61BC-C   1/2							
B A							

	т	۵	П	т		D	0	Φ		⊳	_
		Contact Layout					Panel cutout				
4	- <u>×</u>	$\begin{array}{c} & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ & & & \\ & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & &$					JAM NUT RECEPTACLE (TYPE 7)	۸ ۵			4
	B +.314 (7.98)	Y-axis (mm)     Contact position ID     X-axis (mm)     Y-axis (mm)       +.500 (12.70)     i     +.251 (6.38)    314       +.435 (11.05)     j     +.133 (3.38)    379	1) 7.98) 9.63)					V			_
S	$\begin{array}{cccc} &+413(10.49)\\ & D &+485(12.32)\\ & E &+527(13.39)\\ & F &+536(13.61)\\ & G &+511(12.98)\\ & H &+454(11.53)\\ & J &+368(9.35)\\ & K &+259(6.58)\\ & L &+134(3.40)\\ & M &+000(0.00)\\ & N &-134(3.40)\\ & M &+000(0.00)\\ & N &-134(3.40)\\ & P &-259(6.58)\\ & R &-368(9.35)\\ & S &-454(11.53)\\ & T &-511(12.98)\\ & U &-536(13.61)\\ & V &-527(13.39)\\ & W &-485(12.32)\\ & X &-413(10.49)\\ & Y &-314(7.98)\\ & Z &-196(4.98)\\ & a &-068(1.73)\\ & b &+068(1.73)\\ & b &+362(9.19)\\ & \end{array}$	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	7.98) 5.41) 2.24) 1.17) 4.45) 7.19) 9.22) 8.59) 5.66) 3.00 0.25) 3.53) 5.52) 6.78) 5.52) 5.53) 5.5				Dim     Nominal       B     43.43+0/-0.25       ØC     44.7+0.25/-0				3
	h	213 (5.41)	rsedes				SOURIAU shall not be liable f due to a use of the Produc the Specifications issued by eit (professional recomme	ts which does not con her of the Parties or by	nply with y a third party		
N							C		ction & Control List Not Listed		2
				PN: 8D725S61BC							
	A 04-10-2016 First Release							-			
						ISS DATE Designed By:	Latest modification - by Date:		CUSTOMER DRAWI	MOD N°	-
						TITLE	Stainless	Steel Receptad	cle 8D series		-
_						SCALE -	General lin Tolerance		NPRDS / PROJECT <b>859</b>	-	-
						SOURIAU	WWW.SOURIA	U.COM	This document is th SOURIA it must not be rep communicated with	AU produced or	
					I	FORMAT A3		AU DRG N° 5S61BC-C		SHEET 2/2	
	Н	G	F	E		D	C	В		A	L