

Henkel Corporation

Digi-Key Corporation 16166 125th Ave NE Thief River Falls, MN 56701-8489 United States

Date:

09/11/2021

Dear Valued Customer:

Enclosed please find a new or revised Safety Data Sheet(s) (SDSs). You are receiving this/these in accordance with country/regional regulatory requirements.

Item Number

IDH Number

**Product Description** 

1993881

LOCTITE GC 10 SAC305T4 885V 52U

2041005

LOCTITE GC 3W SAC305T3 895V 52U

Previous versions of these documents should be replaced by the newer version.

SDSs should be forwarded to personnel responsible for workplace safety and to employees who will be handling this/these product(s) to ensure awareness and understanding of safety concerns and regulatory responsibilities. SDSs must also be forwarded on to your customers if you further distribute or resell the product.

If you have any questions, please contact your local Product Safety and Regulatory Affairs Specialist.

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

Sincerely,

Henkel Product Safety and Regulatory Affairs



Revision Number: 007.0

Issue date: 12/23/2019

### PRODUCT AND COMPANY IDENTIFICATION

Product name:

**LOCTITE GC 10 SAC305T4 885V 52U** 

Product type/use:

Solder Paste

1993881

Restriction of Use:

None identified

Region:

IDH number:

**United States** 

Company address:

Contact information:

Henkel Corporation One Henkel Way

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

Rocky Hill, Connecticut 06067

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

### HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

DANGER:

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING

DIFFICULTIES IF INHALED.

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2A
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1

#### PICTOGRAM(S)



#### **Precautionary Statements**

Prevention:

Avoid breathing dust or fumes. Wash affected area thoroughly after handling. Contaminated

work clothing should not be allowed out of the workplace. Wear protective gloves, eye

Response:

protection, and face protection. In case of inadequate ventilation wear respiratory protection. IF ON SKIN: Wash with plenty of water. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. If experiencing respiratory symptoms: Call a poison center or physician.

Wash contaminated clothing before reuse.

Storage:

Not prescribed

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

Product name: LOCTITE GC 10 SAC305T4 885V 52U IDH number: 1993881

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Tin	7440-31-5	80 - 100
Silver	7440-22-4	1 - 5
rosin	8050-09-7	1-5
Polyethylene glycol dibutyl ether	31885-97-9	1 - 5
Triethylene glycol monobutyl ether	143-22-6	1 - 5
Dodecane-1-thiol	112-55-0	0.1 - 1

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. Get immediate medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). If symptoms develop and persist, get

medical attention. Wash clothing before reuse.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious

person. If symptoms develop and persist, get medical attention.

Symptoms: See Section 11.

### 5. FIRE FIGHTING MEASURES

**Extinguishing media:** Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear a self-contained breathing apparatus with a full face piece operated in

pressure-demand or other positive pressure mode. Do not use water on fires

where molten metal is present.

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon. Metal oxide fumes. Formaldehyde. High temperatures may

produce heavy metal dust, fumes or vapors. The flux will give rise to irritating

fumes.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Ensure adequate ventilation. Wear protective clothing, gloves and safety

glasses. Scrape up spilled material and place in a closed container for disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to

clean up.

### 7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Wear suitable protective clothing, gloves

and eye/face protection. Avoid contact with eyes, skin and clothing. Avoid skin contact with molten resins. When using, do not eat, drink or smoke. Wash

thoroughly after handling.

Storage: For safe storage, store between -20 °C (-4°F) and 50 °C (122°F)

Store in original container until ready to use. Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed

until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Tin	2 mg/m3 TWA Inhalable fraction.	2 mg/m3 PEL (as Sn)	None	None
Silver	0.1 mg/m3 TWA Dust and fume.	0.01 mg/m3 PEL (as Ag)	None	None
rosin	Exposure by all routes should be carefully controlled to levels as low as possible.  Included in the regulation but with no data values. See regulation for further details (Respiratory sensitization) (Dermal sensitization)	None	None	None
Polyethylene glycol dibutyl ether	None	None	None	None
Triethylene glycol monobutyl ether	None	None	None	None
Dodecane-1-thiol	0.1 ppm TWA (Dermal sensitization)	None	None	None

Engineering controls: Use adequate ventilation to remove molten vapors or fumes. Provide

adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid Color: Gray

Odor: Mild Odor threshold: Mild Not available.

pH: Not available.

Vapor pressure: 0.83 Pa (50 °C (122°F))

Boiling point/range: Not available.

Melting point/ range: 217 °C (422.6 °F)

Specific gravity:

IDH number: 1993881 Product name: LOCTITE GC 10 SAC305T4 885V 52U

4.5

Vapor density:

Flash point:

Flammable/Explosive limits - lower: Flammable/Explosive limits - upper:

Autoignition temperature:

Flammability: **Evaporation rate:** 

Solubility in water:

Partition coefficient (n-octanol/water):

**VOC** content:

Viscosity:

**Decomposition temperature:** 

Not available.

131 °C (267.8 °F)

Not available.

Not available.

Not available.

Not applicable Not available.

Not available.

Not available.

3.62 % Not available.

Not available.

# 10. STABILITY AND REACTIVITY

Stability:

Stable under normal conditions of storage and use.

Hazardous reactions:

Will not occur.

Hazardous decomposition

products:

Oxides of carbon. Metal oxide fumes. Thermal decomposition can lead to release of irritating

gases and vapors. Formaldehyde.

Incompatible materials:

Strong oxidizing agents. Acids and bases. Reacts with alkalis: spontaneous decomposition

and production of heat

Reactivity:

Not available.

Conditions to avoid:

Solder alloy will react with concentrated nitric acid to produce toxic fumes of nitrogen oxides.

# 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes

IDH number: 1993881

Product name: LOCTITE GC 10 SAC305T4 885V 52U

Page 4 of 6

#### Potential Health Effects/Symptoms

Inhalation:

Inhalation of processing fumes may be harmful. May cause allergic respiratory reaction. Excessive exposure to tin fumes or dust may cause Stannosis, a chronic respiratory disease resulting in reduced lung capacity and benign tumors. Excessive inhalation of fumes from many metals can produce an acute reaction known as "metal fume fever". Symptoms consist of chills and fever (very similar to and easily confused with flu symptoms) which come on a few hours after large exposures. Fumes and/or dust produced by this product may be hazardous in case of ingestion or inhalation. Rosin thermal decomposition product (as formaldehyde) is classified

by NIOSH as a potential occupational carcinogen.

Skin contact:

May cause skin irritation. May cause allergic skin reaction. Argyria (a non-toxic, cosmetic blue-

gray discoloration of the skin and mucous membranes that is irreversible).

Eye contact:

Causes serious eye irritation.

Ingestion:

Not expected under normal conditions of use.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Tin	None	Gastrointestinal, Irritant, Kidney, Liver, Lung, Nervous System
Silver	Oral LD50 (Rat) = > 5,000 mg/kg Dermal LD50 (Rat) = > 2,000 mg/kg	Allergen, Eyes, Irritant, Respiratory, Skin
rosin	None	Allergen, Irritant, Respiratory
Polyethylene glycol dibutyl ether	None	No Records
Triethylene glycol monobutyl ether	Oral LD50 (Rat) = 5,300 mg/kg	Central nervous system, Irritant
Dodecane-1-thiol	Oral LD50 (Mouse) = 4,225 mg/kg	Allergen, Central nervous system, Irritant, Reproductive

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Tin	No	No	No
Silver	No	No	No
rosin	No	No	No
Polyethylene glycol dibutyl ether	No	No	No
Triethylene glycol monobutyl ether	No	No	No
Dodecane-1-thiol	No	No	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** 

Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal. Do not

dispose of in an uncontrolled manner.

Hazardous waste number:

D011. Silver.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:

Not regulated

Hazard class or division:

None

Identification number:

None

Packing group:

IDH number: 1993881

None

International Air Transportation (ICAO/IATA)

Proper shipping name:

Not regulated

Hazard class or division: Identification number:

None None

Packing group:

None

Water Transportation (IMO/IMDG)

Proper shipping name:

Not regulated

Hazard class or division: Identification number:

None None

Packing group:

None

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status:

All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification:

Glycol Ether (CAS# 31885-97-9).

CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312:

None above reporting de minimis.

Immediate Health, Delayed Health

**CERCLA/SARA Section 313:** 

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Silver (CAS# 7440-22-4). Triethylene glycol monobutyl ether (CAS# 143-22-6).

California Proposition 65:

This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm.

**Canada Regulatory Information** 

**CEPA DSL/NDSL Status:** 

One or more components are not listed on, and are not exempt from listing on either the

Domestic Substances List or the Non-Domestic Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by:

Product Safety and Regulatory Affairs

Issue date:

12/23/2019

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

IDH number: 1993881

Product name: LOCTITE GC 10 SAC305T4 885V 52U

Page 6 of 6



Revision Number: 002.3

Issue date: 10/12/2017

### PRODUCT AND COMPANY IDENTIFICATION

Product name:

One Henkel Way

**LOCTITE GC 3W SAC305T3 895V 52U** 

IDH number:

2041005

Product type:

Solder Paste

Region:

**United States** 

Restriction of Use: Company address: Henkel Corporation

Rocky Hill, Connecticut 06067

None identified

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

### HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

DANGER:

CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING

DIFFICULTIES IF INHALED.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1

#### PICTOGRAM(S)



#### **Precautionary Statements**

Prevention:

Avoid breathing dust or fumes. Wash affected area thoroughly after handling. Contaminated

work clothing should not be allowed out of the workplace. Wear protective gloves, eye

Response:

protection, and face protection. In case of inadequate ventilation wear respiratory protection. IF ON SKIN: Wash with plenty of water. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. If experiencing respiratory symptoms: Call a poison center or physician. Take

off contaminated clothing.

Storage:

Not prescribed

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

IDH number: 2041005 Product name: LOCTITE GC 3W SAC305T3 895V 52U See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Tin	7440-31-5	80 - 90
Resin acids and Rosin acids, ethoxylated	8050-33-7	1 - 5
Silver	7440-22-4	1-5
Rosin	8050-09-7	0.1 - 1
Triethylene glycol monobutyl ether	143-22-6	0.1 - 1
Ethylene glycol monophenyl ether	122-99-6	0.1 - 1
Copper	7440-50-8	0.1 - 1
Dodecane-1-thiol	112-55-0	0.1 - 1

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. If symptoms develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). If symptoms develop and persist, get

medical attention. Wash clothing before reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. If symptoms develop

and persist, get medical attention.

Symptoms: See Section 11.

### 5. FIRE FIGHTING MEASURES

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon. Oxides of Metals in Section 3. Formaldehyde. High

temperatures may produce heavy metal dust, fumes or vapors. The flux will

give rise to irritating fumes.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Ensure adequate ventilation. Wear suitable protective clothing, gloves and

eye/face protection. Scrape up spilled material and place in a closed container

for disposal.

### 7. HANDLING AND STORAGE

Handling:

Use only in well-ventilated areas. Wear suitable protective clothing, gloves and eye/face protection. Avoid contact with eyes, skin and clothing. Avoid skin contact with molten resins. When using, do not eat, drink or smoke. Wash

thoroughly after handling.

Storage:

For safe storage, store between 15 °C (59°F) and 30 °C (86°F)

Store in a cool, dry, well-ventilated area. Store in original container until ready

to use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Tin	2 mg/m3 TWA	2 mg/m3 PEL (as Sn)	None	None
Resin acids and Rosin acids, ethoxylated	None	None	None	None
Silver	0.1 mg/m3 TWA Dust and fume.	0.01 mg/m3 PEL (as Ag)	None	None
Rosin	Exposure by all routes should be carefully controlled to levels as low as possible. Included in the regulation but with no data values. See regulation for further details (Respiratory sensitization) (Dermal sensitization)	None	None	None
Triethylene glycol monobutyl ether	None	None	None	None
Ethylene glycol monophenyl ether	None	None	None	25 ppm (SKIN)
Copper	0.2 mg/m3 TWA (as Cu) Fume. 1 mg/m3 TWA (as Cu) Dust and mist.	1 mg/m3 PEL (as Cu) Dust and mist. 0.1 mg/m3 PEL (as Cu) Fume.	None	None
Dodecane-1-thiol	0.1 ppm TWA (Dermal sensitization)	None	None	None

Engineering controls:

Heat only in areas with appropriate exhaust ventilation. Provide adequate local

exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Heat and chemical resistant gloves.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Solid, Paste

Color: Odor: Gray Mild

Odor threshold:

Not available.

pH:

Not available.

Vapor pressure:

< 0.1 mbar (50 °C (122°F))

Boiling point/range:

244 °C (471.2 °F)

IDH number: 2041005

Product name: LOCTITE GC 3W SAC305T3 895V 52U

Melting point/ range:

Specific gravity:

Vapor density:

Flash point:

Flammable/Explosive limits - lower: Flammable/Explosive limits - upper:

Autoignition temperature: Flammability:

**Evaporation rate:** Solubility in water:

Partition coefficient (n-octanol/water):

**VOC** content: Viscosity:

**Decomposition temperature:** 

217 °C (422.6 °F)

4.46

Not available.

126 °C (258.8 °F): Product is a solid.

Not available.

Not available.

Not available. Not applicable

Not available. Partially soluble

Not available.

2.33 % Not available.

Not available.

# 10. STABILITY AND REACTIVITY

Stability:

Stable under normal conditions of storage and use.

Hazardous reactions:

Will not occur.

Hazardous decomposition

products:

Oxides of carbon. Oxides of Metals in Section 3. Thermal decomposition can lead to release of

irritating gases and vapors. Formaldehyde.

Incompatible materials:

Strong oxidizing agents. Strong acids and strong bases.

Reactivity:

Not available.

Conditions to avoid:

Solder alloy will react with concentrated nitric acid to produce toxic fumes of nitrogen oxides.

### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes

#### Potential Health Effects/Symptoms

Inhalation: Inhalation of processing fum

Inhalation of processing fumes may be harmful. May cause allergic respiratory reaction. Excessive exposure to tin fumes or dust may cause Stannosis, a chronic respiratory disease resulting in reduced lung capacity and benign tumors. Excessive inhalation of fumes from many metals can produce an acute reaction known as "metal fume fever". Symptoms consist of chills and fever (very similar to and easily confused with flu symptoms) which come on a few hours after large exposures. Fumes and/or dust produced by this product may be hazardous in case of ingestion or inhalation. Rosin thermal decomposition product (as formaldehyde) is classified

by NIOSH as a potential occupational carcinogen.

Skin contact:

Causes skin irritation. May cause allergic skin reaction. Argyria (a non-toxic, cosmetic blue-gray

discoloration of the skin and mucous membranes that is irreversible).

Eye contact:

Causes serious eye irritation.

Ingestion:

Not expected under normal conditions of use.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects  Gastrointestinal, Irritant, Kidney, Liver, Lung, Nervous System	
Tin	None		
Resin acids and Rosin acids, ethoxylated	None	No Records	
Silver	Oral LD50 (Rat) = > 5,000 mg/kg Dermal LD50 (Rat) = > 2,000 mg/kg	Allergen, Eyes, Irritant, Respiratory, Skin	
Rosin	None	Allergen, Irritant, Respiratory	
Triethylene glycol monobutyl ether	Oral LD50 (Rat) = 5,300 mg/kg	Central nervous system, Irritant	
Ethylene glycol monophenyl ether	Oral LD50 (Rat) = 1,260 mg/kg Oral LD50 (Rat) = 13,700 mg/kg Oral LD50 (Mouse) = 16,500 mg/kg	Blood, Central nervous system, Developmental, Irritant, Kidney, Reproductive	
Copper	None	Allergen, Blood, Central nervous system, Developmental, Gastrointestinal, Immune system, Irritant, Kidney, Liver, Mutagen, Sensory, Skin	
Dodecane-1-thiol	Oral LD50 (Mouse) = 4,225 mg/kg	Allergen, Central nervous system, Irritant, Reproductive	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)	
Tin	No .	No	No	
Resin acids and Rosin acids, ethoxylated	No	No	No	
Silver	No	No	No	
Rosin	No	No	No	
Triethylene glycol monobutyl ether	No	No	No	
Ethylene glycol monophenyl ether	No	No	No	
Copper	No	No	No	
Dodecane-1-thiol	No	No	No	

# 12. ECOLOGICAL INFORMATION

**Ecological information:** 

IDH number: 2041005

Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal. Do not

dispose of in an uncontrolled manner.

Hazardous waste number:

D011 Silver

### TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:

Not regulated

Hazard class or division:

None

Identification number:

Packing group:

None None

International Air Transportation (ICAO/IATA)

Proper shipping name:

Not regulated

Hazard class or division:

None

Identification number:

None

Packing group:

None

Water Transportation (IMO/IMDG)

Proper shipping name:

Not regulated

Hazard class or division:

None

Identification number:

None

Packing group:

None

# REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification:

None above reporting de minimis

CERCLA/SARA Section 302 EHS:

None above reporting de minimis.

CERCLA/SARA Section 311/312:

Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Silver (CAS# 7440-22-4). Triethylene glycol monobutyl ether (CAS# 143-22-6).

Ethylene glycol monophenyl ether (CAS# 122-99-6).

California Proposition 65:

This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status:

Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

IDH number: 2041005

Product name: LOCTITE GC 3W SAC305T3 895V 52U

Page 6 of 7

Prepared by:

Product Safety and Regulatory Affairs

Issue date:

10/12/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.