

ZCKD17

Limit switch head, Limit switches XC Standard, ZCKD, steel ball bearing mounted roller lever



Main

| | |
|----------------------------|---|
| Range of Product | Telemecanique Limit switches XC Standard |
| Series name | Standard format |
| Product or Component Type | Limit switch head |
| Device short name | ZCKD |
| Head type | Rotary head |
| Product Compatibility | XCKM XCKL |
| Associated body | ZCKLD31 ZCKMD35H29 ZCKL7 ZCKMD39H7 ZCKL8 ZCKL1H7 ZCKM8H7 ZCKM1H7 ZCKM7 ZCKMD37H7 ZCKM9H29 ZCKM5 ZCKMD31 ZCKLD39H7 ZCKL1 ZCKM7H29 ZCKL8H7 ZCKM8 ZCKMD31H29 ZCKL7H7 ZCKLD37 ZCKL6H7 ZCKLD35 ZCKM8H29 ZCKM7H7 ZCKL6 ZCKL5 ZCKLD31H7 ZCKM1 ZCKLD37H7 ZCKMD31H7 ZCKM6H7 ZCKMD37 ZCKL5H7 ZCKM6 ZCKMD37H29 ZCKM9 ZCKMD39 ZCKMD35H7 ZCKMD39H29 ZCKMD35 ZCKM6H29 ZCKLD39 ZCKLD35H7 ZCKM1H29 ZCKM5H29 ZCKM5H7 |
| Movement of operating head | Rotary |
| Type of operator | Roller lever spring return metal ball bearing mounted) |
| Type of approach | Lateral approach, 2 directions |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Complementary

| | |
|------------------|------------|
| Switch actuation | By 30° cam |
| Positive opening | With |
| Head material | Metal |

Environment

| | |
|---------------------------------------|----------------------------|
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Environmental characteristic | Standard environment |

Ordering and shipping details

| | |
|-----------------------|---------------------------------|
| Category | 22416 - LIMIT SWITCHES,IEC,XCKL |
| Discount Schedule | T |
| GTIN | 3389110646764 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 3.46 oz (98 g) |
| Returnability | No |
| Country of origin | FR |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 1.26 in (3.2 cm) |
| Package 1 width | 2.44 in (6.2 cm) |
| Package 1 Length | 2.95 in (7.5 cm) |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 40 |
| Package 2 Weight | 9.14 lb(US) (4.145 kg) |
| Package 2 Height | 5.91 in (15 cm) |
| Package 2 width | 11.81 in (30 cm) |
| Package 2 Length | 15.75 in (40 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|