


NOTES:


MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ" GOLD PLATED



OPE	ERATING TEMPERATURE:	-55°C ~ 125°C
	VER/CO-AX CONTACT RATING: PRESENT)	10A (CURRENT)
	NAL CONTACT CURRENT RATING: NAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.
	ULATOR RESISTANCE: LECTRIC	$5000M\Omega$ min.

.XX ±0.13 .XXX ±0.05



	COMBINATION D-SUB		SW REFERENCE NO.: 629 COMBO ASSEMBLY		
			DRAWN: C.B	DATE: JAN. 01/20	19
			CHECKED:	DATE:	
0	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
ES CY.	YOUR CONNECTION TO QUALITY & SERVICE	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE: OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 629-27W2650-1ND		ISSUE
			PART NUMBER: 629-27W	2650-1ND	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY

YOUR C		EDAC INC TORONTO, ONT CANADA QUALITY & SERV

WITHSTANDING VOLTAGE:

1000V AC rms

