


MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ GOLD PLATED
OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	30A (CURRENT)
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.
INSULATOR RESISTANCE: DIELECTRIC	5000MΩ min.

SW REFERENCE NO .: 630 COMBO ASSEMBLY COMBINATION D-SUB C.B DATE: JAN. 01/2019 DRAWN: CHECKED: DATE: THESE DRAWINGS AND SPECIFICATIONS (IN C.A.D. 1:1) OF 2 SCALE: SHEET 1 EDAC INC ARE THE PROPERTY OF EDAC INC. AND TORONTO, ONTARIO SHALL NOT BE REPRODUCED, OR COPIED 630-2W2-640-3NC DRAWING NUMBER: ISSUE OR USED AS THE BASIS FOR THE CANADA MANUFACTURE OR SALE OF APPARATUS 1 YOUR CONNECTION TO QUALITY & SERVICE PART NUMBER: 630-2W2-640-3NC WITHOUT WRITTEN PERMISSION.






THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



.XX

INSUL DIELE WITHSTANDING VOLTAGE:

1000V AC rms



ISSUE NUMBER

(1)

