

product type designation

product description

PROFIBUS Cable 830-2

Plug-in cable comprising PROFIBUS standard cable, preferred length, preassembled with two 9-pole connectors

plug-in cable 830-2 for PROFIBUS, pre-assembled cable with two D-sub connectors 9-pole, Terminating resistors connectable, 10 m.



suitability for use

Cable for connecting PROFIBUS stations (e.g. HMI) to automation devices

cable designation

02YSY (ST) CY 1x2x0,64/2,55-150 VI KF 40 FR

wire length

10 m

electrical data

number of electrical connections

2

attenuation factor per length

- at 9.6 kHz / maximum 0.0025 dB/m
- at 38.4 kHz / maximum 0.004 dB/m
- at 4 MHz / maximum 0.022 dB/m
- at 16 MHz / maximum 0.042 dB/m

operating voltage

- RMS value 80 V

mechanical data

number of electrical cores

2

design of the shield

Overlapped aluminum-clad foil, sheathed in a braided screen of tin-plated copper wires

outer diameter

- of inner conductor 0.65 mm
- of the wire insulation 2.55 mm
- of the inner sheath of the cable 5.4 mm

material

- of the wire insulation polyethylene (PE)
- of the inner sheath of the cable PVC

color

- of the insulation of data wires red/green

bending radius

- with single bend / minimum permissible 37.5 mm
- with multiple bends / minimum permissible 75 mm

weight per length

80 kg/km

ambient conditions

ambient temperature

- note Electrical properties measured at 20 °C, tests according to DIN 47250 part 4 respectively DIN VDE 0472

fire behavior

flame resistant according to IEC 60332-3-24 (Category C) and UL 1685 (CSA FT 4)

chemical resistance

<ul style="list-style-type: none"> • to mineral oil • to water 	oil resistant according to IEC 60811-2-1 (4 h / 70°C) conditional resistance
radiological resistance / to UV radiation	resistant
protection class IP	IP20
standards, specifications, approvals	
UL/ETL listing / 300 V Rating	Yes; c(UL)us, CMG / CL3 / Sun Res
UL/ETL style / 600 V Rating	Yes
certificate of suitability	
<ul style="list-style-type: none"> • EAC approval • CE marking • RoHS conformity 	Yes Yes Yes
Marine classification association	
<ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • French marine classification society (BV) • Det Norske Veritas (DNV) • Germanische Lloyd (GL) • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) • Polski Rejestr Statkow (PRS) 	No No No No No No No
reference code	
<ul style="list-style-type: none"> • according to IEC 81346-2 • according to IEC 81346-2:2019 	WG WGB
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Selection guide for cables and connectors • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support 	http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter https://sie.ag/2QdlxcP http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
last modified:	12/31/2021 