т <u>Ω</u> т		0	∞ >		
		LAYOUT SHOWN AS EXA	MPLE		
Keying Shown as example					
CHARACTERISTICS Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III Dim Nominal					
-Shell Material : Aluminium -Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer		Country	Jurisdiction & Control List		
-Contact Plating : Gold over copper Alloy 0.8μm minimum		FR	Not Listed		
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories		PN: 8D511F04SE			
-Temperature Range - 65°C to +200°C	A 15-10-201	6 First Release			
-Salt Spray : 48 hours					
Mass : 17.86 g ± 10%	ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
TITLE Aluminium Plug 8D se		m Plug 8D series			
BASIC SERIES: 8D 5 - 11 F 04 S E	SCALE	General linear	NPRDS / PROJECT		
SHELL TYPE : Plug with RFI Shielding	NA	Tolerances:	859		
			This document is the p SOURIAU	roperty of	
SHELL SIZE : 11 CONTACT TYPE : SOCKET(500	SOURIAU	J WWW.SOURIAU.COM it must not be reproduced or communicated without permission			
PLATING : F = Nickel CONTACT LAYOU		SOURIAU D		SHEET	
	A3	8D511F04		1/2	
1					

ſ	Ξ	G	г П	m		0	
		Contact Layout					
4	-X	$ \begin{array}{c} $					
	Shell Arrangement Numb	X-axis Y-axis (mm) +0.65 (1.65) +0.65 (1.65) +0.65 (1.65) -0.65 (1.65) -0.65 (1.65) -0.65 (1.65) -0.65 (1.65) +0.65 (1.65)	1				
ω	11 -4 4]				
	+					SOURIAU shall not be lia due to a use of the Pro the Specifications issued b	oducts w y either c
М						(professional reco PN: 8	Count FR
					A 15-10-20 ISS DATE Designed By:	116 First Release Latest modification - by Date:	
_ _					SCALE NA	Gener 	Alumir ral linear grances: ±
					FORMAT		RIAU.(JRIAL
	Н	G	F	E	A3	8D)511F

