	m m		0	B	
A					
			LAYOUT SHOWN AS EXAMIN	PLE	
	Keying Shown as example				
CHARACTERISTICS	Connector dimension	1			
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal ØS 48 Max	-			
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	Z 31 Max VV THREAD M37x1-6g		SOURIAU shall not be liable for any nor due to a use of the Products which d the Specifications issued by either of the (professional recommendation, t	loes not comply with Parties or by a third party	
-Seals & Grommet : Silicon Elastomer			Country FR	Jurisdiction & Control List Not Listed	
 Contact Plating : Gold over copper Alloy 0.8μm minimum Durability : 500 Mating cycles Delivered with Souriau contacts and Accessories 			PN: 8D525F61		
-Temperature Range : -65°C to +200°C		A 06-10-20 ⁷	16 First Release		
-Salt Spray : 48 hours		ISS DATE	Latest modification - by		MOD N°
		Designed By:	Date:	CUSTOMER DRAWING	
		TITLE	Aluminium	n Plug 8D series	
→ BASIC SERIES: 8D 5 - 25 F SHELL TYPE : Plug with RFI Shielding	61 A D	SCALE	General linear Tolerances:	NPRDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact			J WWW.SOURIAU.COM	it must not be reproduced	lor
SHELL SIZE : 25	CONTACT TYPE : PIN(50			communicated without perm	
PLATING : F = Nickel	CONTACT LAYO	OUT : 25-61 A3	SOURIAU DE		SHEET
			8D525F61A		1/2

