

www.lemo.com

# CNB.M06.GLLR

## **SUMMARY**

#### # Wires

Low voltage 6



Image is for illustrative purpose only

Series 2P

Termination type Female solder

IP rating 66

AWG wire size 28.00 - 20.00 Cable Ø 3.20 - 9.20 mm

Status active

### **Download**

Request a quote

Catalog

## **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model CN\*: Fixed receptacle, nut fixing, watertight (IP 66)

Keying 3 keys (alpha=0, gamma=60; Plug: male contacts; Receptacle: female contacts)

Housing Material PSU (Polysulfone), gray

Weight 5.48 g

### **Performance**

Configuration 2P.M06: 6 Low V.

Insulator L: PEEK for solder contacts

Rated Current 12 Amps

### **Specifications**

Contact Type: Solder

Contact Dia.: 1.3 mm (0.051in) Bucket Dia.: 1.1 mm (0.043in)

Test voltage (kV rms) Contact-contact: 1.35

Air clerance min.: 1.2 mm Creepage distance min.: 1.2 mm

#### **Others**


LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


Endurance (Shell): >1000 mating cycles


F ret (min): 150 N F ret (max): 250 N

Steam sterilization: 20 times

# **DRAWINGS**







### **Dimensions**

	А	L	N
mm.	20.2	28.7	23.8
in.	0,80	1,13	0,94

# **RECOMMENDED BY LEMO**

#### **Tools**

### **Cables**

CMN.06.T20.062PGZE		Grey	<b>&gt;</b>
CMN.06.T20.062PNZE			>€
CMN.06.T20.062QGZE	TPR (medical)	Grey	▶€
CMN.06.T26.037QGZE	TPR (medical)	Grey	<b>&gt;</b>

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

CMN.06.T28.042QBCE	TPR (medical)		
CMN.06.T28.044PGZE		Grey	<b>&gt;</b>
CMN.06.T28.044PNZE			<b>&gt;</b>
106220	PVC	Black	
106240	PTFE	White	<b>&gt;</b>
12080	PVC	Grey	
160140	PVC	Grey	-5-
160240	PVC	Black	-
160260	PVC	Black	-
260250	PVC	Grey	<b>&gt;</b> =====
360500	PVC	Grey	<b>&gt;</b> ====
360750	PVC	Grey	<b>&gt;</b> ====
60260	PTFE	White	<b>&gt;</b>
6280	PVC	Black	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.