



Performance:

- a. Insertion Loss: <0.3dB
- b. Return Loss: >20dB
- c. Fiber Extension: -100nm,H,+100nm
- d. Ferrule End-Face Radius: 7<R<25mm
- e. Aper Offset: ≤50um
- f. Increase in insertion Loss after 500 mating: 0.2 dB max
- g. Operation Temperature: -40°C to +70°C
- h. Storage Temperature: -40°C to +85°C
- i. The bend radius must respect a minimum of 30mm
- ① j. Mating cycle: 500times

WSW order code: DK-2633-xx

Cable length:  
 01: 1000+50/-0    07: 7000+100/-0  
 02: 2000+100/-0    10: 10000+100/-0  
 03: 3000+100/-0    15: 15000+150/-0  
 05: 5000+100/-0

No.	Specifications	Qty.
④ ③ ① ①	2.8X5.7 mm 2F, MM62.5/125 Duplex cable/ LSZH/ Orange	1
②	3.0mm LC/PC MM Connector/Beige	4
③	LC Duplex Clip/Beige	2
④	LC 3.0mm Boot/Beige	4
⑤	Tail Identification Marker (3mm C-Clip)/NO.A2.A1;B2;B1	4
⑥	LC Heatshrink Tube/Black	2

**RoHS compliant**  
Unit: mm

Scale	Free					Date	Name	Customer-No.
TOLERANCE		④	Update the cable OD	05.06.2019	Segal	Drawn	22.06.2016	ASSMANN WSW-No. <b>DK-2633-xx</b>
		③	Update the cable description	11.12.2018	Segal	Approved	05.06.2019	
		②	Update	09.02.2018	Tom			
DIM	TOL	①	Change the specification	22.01.2018	Tom			Drawing-No.
		①	Drawn	22.06.2016	Amy			<b>ASS 7672 CA</b> rev04
Angle	TOL	Id.	Modification	Date	Name			Replace
								Sheet