



Click [here](#) for the 3D model.

Dimensions

L	450mm NOM
W	300mm NOM
H	220mm NOM
L1	200mm NOM
W1	330mm NOM
W2	370mm NOM
U	100mm NOM
X	15mm NOM
Y	80mm NOM
Z	110mm NOM
I	20mm NOM
J	35mm NOM
K	35mm NOM
N	14mm NOM
M (Earth)	Threaded Studs M12

Packaging Specifications

Packaging	Bulk
Packaging Quantity	1
Component Weight	55000 g

General Information

Series	FLLD3-PV
Style	Chassis Mount
Description	EMI Filter, Chassis Mount, With Y Capacitor
Features	Three Phase, High Performance, High Voltage
Phase	Three-phase
RoHS	Yes
Qualifications	IEC/EN 60939, UL 1283
Terminal Type	Threaded Studs M12

Specifications

Voltage AC	520 VAC
Rated Frequency	50-60 Hz
Rated Current	2500 A (50°C)
Rated Temperature	50°C
Temperature Range	-40/+100°C
Climate Category	40/100/21
Test Voltage DC (P to P)	2250 VDC
Test Voltage DC (P to E)	3000 VDC
Power Loss	230 W (25°C 50 Hz)
Leakage Current	5 mA (MAX)