ت	т	m	D	0			
	ØS						
				LA	YOUT SHOWN AS EXAMPLE		
	Keying Shown as e	xample					
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	F	Connector dimension Dim Nominal					
-Shell Material : Composite -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy		ØS 35.7 Max Z' 31.5 Max /V THREAD M25x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum					Country . FR	urisdiction & Control List Not Listed	
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories					PN: 8D517J26SE		
-Temperature Range : -65°C to +175°C			A 14	4-10-2016 First Release			
-Salt Spray : 2000 hours - Mass : 36.3 g ± 10%			ISS Designed E	DATE Latest modification		CUSTOMER DRAWING	MOD N°
			т	TLE	Composite Plu	g 8D series	
BASIC SERIES: 8D 5 - 17 J SHELL TYPE : Plug with RFI Shielding	26 S E		SCALE		General linear Tolerances: ±	NPRDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact		ORIENTATION : E	- 300	RIAU WWW	SOURIAU.COM	This document is the pr SOURIAU it must not be reprod	uced or
SHELL SIZE : 17 PLATING : J = Olive drab Cadmium		CONTACT TYPE : SOCKET(500 Matings) CONTACT LAYOUT : 17-26	FORMAT		SOURIAU DRG		SHEET
			A3		8D517J26SE-0	•	1/2

