



Click [here](#) for the 3D model.

| Dimensions | |
|------------|-----------------|
| L | 7.2mm -0.5mm |
| H | 7.5mm -0.5mm |
| T | 3.5mm -0.5mm |
| S | 5mm +/-0.4mm |
| LL | 4mm +2mm |
| F | 0.5mm +/-0.05mm |
| G | 0.5mm NOM |

| Packaging Specifications | |
|--------------------------|------|
| Packaging | Bulk |
| Packaging Quantity | 2000 |

| General Information | |
|---------------------|---|
| Series | F611 |
| Dielectric | Metallized Polyester |
| Style | Radial |
| Features | MKT (Wound), DC Multipurpose Applications |
| RoHS | Yes |
| Lead | Wire Leads |
| AEC-Q200 | No |
| Component Weight | 0.2 g |
| Miscellaneous | The Rated Voltage Decreases 1.25%/C Between +85C And +105C (For +125C, Please Consult KEMET). ClimCat: 55/105/56. |

| Specifications | |
|-----------------------|-------------------------|
| Capacitance | 1 uF |
| Capacitance Tolerance | 10% |
| Voltage AC | 30 VAC |
| Voltage DC | 50 VDC, 37.5 VDC (105C) |
| Temperature Range | -55/+105°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 0.8% 1kHz, 1.2% 10kHz |
| Insulation Resistance | 5 GOhms |
| Max dV/dt | 12 V/us |
| Inductance | 6 nH |