## **HellermannTyton**

## **Specification Sheet**

Part Number: 151-00677



HellermannTyton Connector Clips provide a single method to mount connectors to various surfaces in a variety of applications. Highly engineered designs feature anti-rattle discs, anti-rotation oval fir trees and clamps for mounting on edges.

An assortment of Connector Cips is available to fit the variety of connector slot designs made by most of the largest global connector manufacturers.

Conn. Clip w/Fir Tree, 0.76-5.75mm Panel Thick., 6.25-6.75mm Hole Dia., PA66HIRHS, Natural, 5000/ctn

| Article Number      | 151-00677  |
|---------------------|--|
| Туре                | CC08   |
| Color               | Natural (NA)   |
| Quantity Per        | carton   |
| Product Description | Connector Clips feature various attachment point configurations to<br>accommodate the many connectors on the market. They are first mated<br>with a connector on a wire harness or cable assembly, then secured to<br>a surface using the integrated mount. With so many configurations<br>available, attachment surfaces can be a hole, edge, stud or even<br>another harness assembly. |
| Short Description   | Conn. Clip w/Fir Tree, 0.76-5.75mm Panel Thick., 6.25-6.75mm Hole<br>Dia., PA66HIRHS, Natural, 5000/ctn  |

| Length L (Imperial)                     | 0.99           |
|---|----------------|
| Length L (Metric)                       | 25.2           |
| Fixation Method                         | Fir Tree       |
| Width W (Imperial)                      | 0.78           |
| Width W (Metric)                        | 19.81          |
| Height H (Imperial)                     | 0.81           |
| Height H (Metric)                       | 20.55          |
| Panel Thickness Min (Imperial)          | 0.03           |
| Panel Thickness Max (Imperial)          | 0.23           |
| Panel Thickness Min (Metric)            | 0.7            |
| Panel Thickness Max (Metric)            | 5.75           |
| Mounting Hole Diameter D (Imperial)     | 0.08 x 0.26    |
| Mounting Hole Diameter D (Metric)       | 6.25 - 6.75 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.08           |
| Mounting Hole Diameter D Max (Imperial) | 0.26           |

| Material                     | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
|------------------------------|--|
| Material Shortcut            | PA66HIRHS  |
| UV Resistant (Yes/No)        | No   |
| Operating Temperature        | -40°F to +230°F (-40°C to +110°C)                                |
| Reach Compliant (Article 33) | Yes  |
| ROHS Compliant               | Yes  |
|                              |  |
| Package Quantity (Imperial)  | 5000   |
| Package Quantity (Metric)    | 5000   |
| Customs Number               | 3926909988   |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.