


KEVET
a YAGEO company

A768, Polymer Aluminum, 47 uF, 20%, 25 VDC, -55/+125°C



Click here for the 3D model.

Dimensions	
D	6.3mm +/-0.5mm
L	5.7mm +/-0.3mm
W	6.6mm +/-0.2mm
Н	6.6mm +/-0.2mm
С	7.3mm +/-0.2mm
Р	2mm NOM
R	0.5 - 0.8mm

Packaging Specifications		
Packaging	T&R, 380mm	
Packaging Quantity	1000	

General Information			
Series	A768		
Dielectric	Polymer Aluminum		
Style	SMD Can		
Description	Surface Mount, Polymer Aluminum		
RoHS	Yes		
Lead	V-Chip		
Qualifications	AEC-Q200		
AEC-Q200	Yes		
Halogen Free	Yes		

Specifications	
Capacitance	47 uF
Capacitance Tolerance	20%
Voltage DC	25 VDC, 28.7 VDC (Surge)
Temperature Range	-55/+125°C
Rated Temperature	125°C
Life	2000 Hrs
Resistance	42 mOhms (100kHz 20C)
Ripple Current	1175 mAmps (100kHz 125C)
Leakage Current	235 uA (2min 20°C)
High Temperature Solder	Yes

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.