

In some cases, enabling Local Echo may cause character duplication in Tera Term and Putty. Please keep Local Echo set to Disabled or Auto if this issue is encountered,

3-Port HDMI Mini Switch for Video and Audio, 4K x 2K UHD @ 30 Hz (HDMI F/3xF) with Remote Control

MODEL NUMBER: B119-003-UHD-MN









Connect 3 HDMI source devices, such as a Blu-ray[™] player, video game system and DVR, to a single port on an HDMI monitor and switch back and forth between them. Ideal for home A/V systems, presentations and digital signs.

Description

The B119-003-UHD-MN 3-Port Mini HDMI Switch allows you to connect three HDMI source devices to one port on an HDMI monitor and switch back and forth between them. For instance, you can connect your Blu-ray player, video game system and cable/satellite DVR to one HDMI port on your high-definition television. Or you can connect three computers or media centers to a monitor for displaying digital signage or giving presentations.

Switch between source devices using buttons on the unit or the included remote control. The included IR extender receiver lets you hide the unit out of sight while still being able to switch devices up to 16 feet away using the remote. When the currently used device is powered off, the unit automatically switches to the next powered-on device.

The B119-003-UHD-MN ensures top-quality audio/video applications with Ultra High Definition (UHD) video resolutions up to 3840 x 2160 (4K x 2K) @ 30 Hz and 48-bit True Color (16 bits per channel), as well as DTS-HD, Dolby True-HD and 7.1-channel surround sound audio. It's compatible with 3D, HDCP and EDID. Hassle-free functionality requires no software, drivers or external power supply. Sets up in seconds.

Features

Connects 3 HDMI Devices to 1 HDMI Display

- Switch between source devices via pushbuttons on unit or included remote control
- Ideal for home audio/video applications, presentations and digital signage
- Included IR extender receiver lets you control devices from a distance using the remote
- · Automatically switches to next available device when currently used device is powered off

Highlights

- Switch source devices using buttons or included remote control
- Switches to next port when current device is powered off
- Supports UHD video resolutions up to 3840 x 2160 (4K x 2K)
- Supports DTS-HD, Dolby TrueHD and 7.1-channel surround sound
- No software, drivers or external power supply required

System Requirements

 HDMI-enabled devices and monitor

Package Includes

- B119-003-UHD-MN 3-Port Mini HDMI Switch
- Remote control
- IR extender receiver
- Owner's manual



Features Top-of-the-Line Audio and Video

- Supports Ultra High Definition (UHD) video resolutions up to 3840 x 2160 (4K x 2K) @ 30 Hz
- Supports 48-bit True Color (16 bits per channel)
- Supports DTS-HD, Dolby True-HD and 7.1-channel surround sound audio
- Compatible with HDMI 1.4, 3D, HDCP 1.4 and EDID

Sets Up in Seconds

• Plug and play right from the box with no software, drivers or external power supply needed

Specifications

OVERVIEW		
UPC Code	037332189233	
INPUT		
Bus Powered	Yes	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	Red (1, 2, 3)	
PHYSICAL		
Color	Black	
Material of Construction	ABS	
Rackmountable	No	
Shipping Dimensions (hwd / cm)	13.46 x 6.86 x 2.54	
Shipping Dimensions (hwd / in.)	5.30 x 2.70 x 1.00	
Shipping Weight (kg)	0.12	
Shipping Weight (lbs.)	0.26	
Unit Dimensions (hwd / in.)	0.7 x 3.2 x 2.3	
Unit Packaging Type	Box	
Unit Weight (kg)	0.05	
Unit Weight (Ibs.)	0.12	
ENVIRONMENTAL		
Operating Temperature Range	32 to 113 F (0 to 45 C)	
Storage Temperature Range	14 to 176 F (-10 to 80 C)	
BTUs	3.4 BTU/Hr	
Power Consumption (Watts)	1	



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

WARRANTY	
Certifications	Tested to CE, FCC, RoHS, REACH
CERTIFICATIONS	
Technology	HDMI; IR
Consumer Electronics Control (CEC) Supported	Yes
3D Video Supported	Yes
IR Remote Extension Support	Yes
EDID Compatible	Yes
Max Supported Color Depth	48-bit Deep Color
Driver Required	No
Audio Specification	DTS-HD, Dolby TrueHD and 7.1 Channel Surround Sound
HDCP Specification	1.4
HDMI Specification	1.4
Max Supported Video Resolution	3840 x 2160 @ 30Hz
Port Selection	Pushbutton
FEATURES & SPECIFICATIONS	
Side B - Connector 1	HDMI (FEMALE)
Side A - Connector 1	(3) HDMI (FEMALE)
Ports	3
CONNECTIONS	
Storage Humidity Range	5% to 90% RH, Non-Condensing
Operating Humidity Range	10% to 85 % RH, Non-Condensing

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies