ASDCIATION CONNECTING ELECTRONICS INDUSTRIES® MOUSTRIES® International and Pan-American co	urn. Illinois. All rights reserved	under both This do level pa	ocument is a declaration arts, the declaration	ation of the substar encompasses all 1	ces within the manufactur ower level materials for w	rer listed item. Note hich the manufactu	e: if the item is an as arer has engineering	sembly with lower responsibility.		
IPC Web Site for Information on I http://www.ipc.org/IPC-175x	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute			Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Information						
Supplier Information										
Company name*	pany name* Company unique ID		Unique ID Authority			Response Date*				
onsemi	emi					2023-06-08				
Contact Name	Title - Contact		Phone - Cont	Phone - Contact*			Email - Contact*			
Product-Env-Stewards	Product Enviro Compliance		NA			Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - Representative			Phone - Representative*			Email - Representative*				
Product-Env-Stewards Product Enviro Co		o Compliance		NA			Product-Env-Stewards@onsemi.com			
Requester Item Number Mfr Item	Number Mfr Item Name		Effective Da	te Version	Manufacturing Site	Weight*	UOM	Unit Type		
MC74HC	CT08ADG QUAD 2-INPUT	AND GATE	2023-06-08		PH1	122.04	mg	Each		
Manufacturing Proccess Information			· · ·			·				
Terminal Plating / Grid Array Material T	Terminal Base Alloy J-STD-020 M		g Peak Pro	Peak Process Body Temperature Max Time at Peal		Temperature Number of Reflow Cycles				
Matte Tin (Sn) - annealed CU Alloy 1		1	260	С	30	seconds 3				
Comments										
evel 1 - maximum time at peak temperature during sol	dering is 10-30 seconds									
For more information regarding material composition	please refer to page 3									

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DIBP).								
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted				
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all				
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the				
Supplier Digital Signature Ra	stislav Drska	Le							

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

select a RoHS exemption, if appli	cable [E] enter the weigh			ance category (JIG or Requester) or enter a [F] Optionally enter the positive (+) and n				
sigma range of distribution unless Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.98	mg	Supplier	Silicon (Si)	7440-21-3		0.98	mg
Die Attach	4.44	mg	Supplier	Silver (Ag)	7440-22-4		3.33	mg
			Supplier	Epoxy resins	129915-35-1		1.11	mg
Lead Frame 6	69.62	mg	Supplier	Silver (Ag)	7440-22-4		0.7658	mg
			Supplier	Zinc (Zn)	7440-66-6		0.1392	mg
			Supplier	Iron (Fe)	7439-89-6		1.8101	mg
			Supplier	Copper (Cu)	7440-50-8		66.9048	mg
Mold Compound-Black	43.43	mg		Epoxy resin	proprietary data		2.1715	mg
			Supplier	Phenolic Resin	Proprietary Data		2.1715	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.8686	mg
			Supplier	Carbon Black (C)	1333-86-4		0.2172	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		38.0013	mg
Plating	3.27	mg	Supplier	Tin (Sn)	7440-31-5		3.27	mg
Wire Bond - Cu	0.3	mg	Supplier	Copper (Cu)	7440-50-8		0.3	mg