

## Smart Pro line interactive UPS System - NAFTA assembled version of SMART3000NET

MODEL NUMBER: **SM3000NAFTA**



### Description

Tripp Lite's SM3000NAFTA intelligent, line interactive large tower UPS system protects servers, networking accessories and telecommunications equipment from blackouts, voltage fluctuations and transient surges. Large internal batteries offer 23 minutes half load runtime and 7 minutes fully loaded. Runtime is expandable with optional BP24V28-2U (limit 1) and BP24V70-3U external battery packs. 3000VA/2400 watt power handling capability supports a variety of networking, telecom and other sensitive electronic applications. Includes 8 protected outlets. Supports remote monitoring of UPS and site power conditions via built-in RS-232 enabled monitoring port, plus standard UPS monitoring via 2 built in contact closure ports. Includes PowerAlert UPS monitoring and unattended shutdown software with complete cabling. Built-in audible alarm and front panel LEDs indicate line power, battery power, battery charge level, load level and voltage regulation status. Network grade AC surge suppression protects equipment from damage and performance problems resulting from transient surges. Attractive large gray tower housing. \$250,000 connected equipment insur.

### Features

- SM3000NAFTA line interactive UPS offers battery derived AC output during power outages, voltage regulation during brownouts and overvoltages, plus network-grade AC surge suppression
- 3000VA/2400 watt power handling capability supports a variety of networking, telecom and other sensitive electronic devices
- Large internal batteries offer runtimes of 23 minutes at half load (1500VA/1200 watts) and 7 minutes at full load (3000VA/2400 watts)
- Runtime is further expandable with optional external BP24V28-2U (limit 1) and BP24V70-3U battery packs
- Automatic Voltage Regulation (AVR) circuits maintain 120V nominal output over an input voltage range of 87-140V
- Includes 8 fully protected outlets (4 NEMA 5-15R & 4 NEMA 5-15/20R) with 2 single outlet load banks that can be individually powered off and back on again via software interface
- PowerAlert UPS monitoring and unattended shutdown software enables configurable network broadcast

### Highlights

- 3000VA / 3kVA line interactive, extended-run tower UPS
- Maintains 120V nominal output over an input range of 87 to 140V
- Network communications supported via 3 DB9 ports (1 serial / 2 contact closure)
- Current monitoring and switched PDU control via 2 single-outlet load banks
- Input: L5-30P (120V 30A) / Output: 4 NEMA 5-15/20R, 4 NEMA 5-15R (120V)
- \$250,000 Ultimate Lifetime Insurance (USA, Puerto Rico and Canada only)

### Package Includes

- SMART3000NET UPS System
- PowerAlert Software and three 6 foot network cables
- Warranty information
- Instruction manual



messaging, email notification, event logging and running user defined script commands

- Offers simultaneous monitoring of up to 3 directly connected devices through included DB9 contact closure and RS-232 enabled interfaces, or the monitoring of any number of additional servers over IP with included PowerAlert monitoring software
- In addition to the contact closure monitoring of on battery, low battery and power restored messaging, built-in RS-232 interface supports messaging of UPS and line power status, including AC line voltage, DC battery voltage and remaining battery capacity
- Supports activate self-test and UPS output power control for delayed or immediate reboot of connected equipment
- Diagnostic LEDs (indicate 17 performance conditions)
- UL (USA), cUL (Canada), NOM (Mexico), FCC Class A (Emissions)
- \$250,000 Ultimate Lifetime Insurance (USA & Canada Only)

## Specifications

| OVERVIEW                                 |   |
|--|---|
| UPC Code                                 | 037332137845  |
| OUTPUT                                   |   |
| Output Volt Amp Capacity (VA)            | 3000  |
| Output kVA Capacity (kVA)                | 3   |
| Output Watt Capacity (Watts)             | 2400  |
| Output kW Capacity (kW)                  | 2.4   |
| Power Factor                             | 0.8   |
| Frequency Compatibility                  | 60 Hz   |
| Output Voltage Regulation (Line Mode)    | -13% / +5%  |
| Output Voltage Regulation (Battery Mode) | +/- 5%  |
| Load Management Receptacles              | Three switchable single-outlet 5-15R load banks         |
| Output Circuit Breakers                  | 15A branch rated (x2) - each breaker protects 4 outlets |
| Output AC Waveform (AC Mode)             | Sine wave   |
| Output AC Waveform (Battery Mode)        | PWM sine wave   |
| Nominal Output Voltage(s) Supported      | 120V  |
| Output Receptacles                       | (4) 5-15R; (4) 5-15/20R                                 |
| INPUT                                    |   |



|  |  |
|--|--|
| Rated input current (Maximum Load)           | 22A  |
| Nominal Input Voltage(s) Supported           | 120V AC  |
| UPS Input Connection Type                    | L5-30P   |
| UPS Input Cord Length (ft.)                  | 8  |
| UPS Input Cord Length (m)                    | 2.4  |
| Recommended Electrical Service               | 30A 120V   |
| Input Cord Length (m)                        | 2.4  |
| <b>BATTERY</b>                               |  |
| Full Load Runtime (min.)                     | 7 min. (2400w)   |
| Half Load Runtime (min.)                     | 23 min. (1200w)  |
| External Battery Pack Compatibility          | <a href="http://www.tripplite.com/External-24V-2U-Rack-Tower-Battery-Pack-select-Tripp-Lite-UPS-Systems-BP24V28-2U~BP24V28-2U">BP24V28-2U</a> <a href="http://www.tripplite.com/External-24V-3U-Rack-Tower-Battery-Pack-select-Tripp-Lite-UPS-Systems-BP24V70-3U~BP24V70-3U">BP24V70-3U</a><br>(multi-pack compatible) |
| DC System Voltage (VDC)                      | 24   |
| Battery Recharge Rate (Included Batteries)   | Less than 9 hours from 10% to 90%  |
| <b>VOLTAGE REGULATION</b>                    |  |
| Voltage Regulation Description               | Automatic voltage regulation (AVR) maintains line power operation with an input voltage range of 87 to 140   |
| Overvoltage Correction                       | Input voltages between 127 and 140 are reduced by 12%  |
| Undervoltage Correction                      | Input voltages between 95 and 105 are boosted by 10%   |
| Severe Undervoltage Correction               | Input voltages between 87 and 94 are boosted by 22%  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |  |
| Switches                                     | 2 Switches control off/on power status and alarm-cancel/self-test operation; set of 4 rear-panel switches control system enable and contact closure port inverter shutoff commands   |
| Alarm Cancel Operation                       | Power-fail alarm can be silenced using alarm-cancel switch; once silenced, alarm will re-sound to indicate low-battery status  |
| Audible Alarm                                | Audible alarm indicates power-failure, overload and low-battery conditions   |
| LED Indicators                               | 5 LEDs indicate line power, battery power, overload, voltage regulation and battery low/replace status   |
| <b>SURGE / NOISE SUPPRESSION</b>             |  |
| UPS AC Suppression Joule Rating              | 480  |
| UPS AC Suppression Response Time             | Instantaneous  |
| EMI / RFI AC Noise Suppression               | Yes  |
| <b>PHYSICAL</b>                              |  |



|   |  |
|---|--|
| Installation Form Factors Supported with Included Accessories | Tower  |
| Primary Form Factor   | Tower  |
| UPS Power Module Dimensions (hwd, in.)                        | 17 x 9 x 12.5  |
| UPS Power Module Dimensions (hwd, cm)                         | 43.18 x 22.86 x 31.75  |
| UPS Power Module Weight (lbs.)                                | 89   |
| UPS Power Module Weight (kg)                                  | 40.37  |
| Shipping Dimensions (hwd / in.)                               | 16.50 x 23.00 x 13.00  |
| Shipping Dimensions (hwd / cm)                                | 41.91 x 58.42 x 33.02  |
| Shipping Weight (lbs.)  | 87.00  |
| Shipping Weight (kg)  | 39.46  |
| Cooling Method  | Fan  |
| UPS Housing Material  | PVC  |
| Primary UPS Height (mm)                                       | 432  |
| Primary UPS Width (mm)  | 229  |
| Primary UPS Depth (mm)  | 318  |
| <b>ENVIRONMENTAL</b>  |  |
| Operating Temperature Range                                   | +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius  |
| Storage Temperature Range                                     | +5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius   |
| Relative Humidity   | 0 to 95%, non-condensing   |
| AC Mode BTU / Hr. (Full Load)                                 | 82.4   |
| Battery Mode BTU / Hr. (Full Load)                            | 1219.3   |
| AC Mode Efficiency Rating (100% Load)                         | 99%  |
| <b>COMMUNICATIONS</b>   |  |
| Communications Interface                                      | DB9 Serial; Contact closure  |
| Network Monitoring Port Description                           | Supports detailed monitoring of UPS and site power conditions; contact closure communications via two additional DB9 ports (3 total) |
| PowerAlert Software   | Included   |
| Communications Cable  | 3 DB9 cables included  |
| <b>LINE / BATTERY TRANSFER</b>                                |  |
| Transfer Time   | 2-4 milliseconds   |
| Low Voltage Transfer to Battery Power (Setpoint)              | 87   |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

|   |  |
|---|--|
| High Voltage Transfer to Battery Power (Setpoint)           | 140  |
| <b>SPECIAL FEATURES</b>                                     |  |
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported   |
| Green Energy-Saving Features                                | Greater than 95% efficiency - GREEN UPS; Individually controllable load banks  |
| <b>CERTIFICATIONS</b>                                       |  |
| UPS Certifications  | Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category A (EMI); ROHS (Restriction of Hazardous Substances) |
| <b>WARRANTY</b>   |  |
| Product Warranty Period (Worldwide)                         | 2-year limited warranty  |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico)  | \$250,000 &a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp;                           |

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>