

## Specification Sheet

Part Number: 115-06960



1-Piece Cable Tie/Arrowhead Mount, 9.0" Length, 2.0" Bundle Diameter, PA66, Black, 1,000/pkg

Article Number	115-06960
Type	RT50SFK
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>•An all-in-one bundling and fixing solution reduces costs.</li><li>•High-specification materials and superior design suit the fixing and bundling needs of complex applications.</li><li>•Releasable to provide quick access to bundles.</li></ul>
Quantity Per	bag

### Product Description

One-piece mounting ties offer a complete solution by bundling cables while at the same time providing a mounting solution. This tie features an extended pawl, allowing the user to release the tie for bundle maintenance. Push mount ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

**Short Description**

1-Piece Cable Tie/Arrowhead Mount, 9.0" Length, 2.0" Bundle Diameter, PA66, Black, 1,000/pkg

**Global Part Name**

RT50SFK-PA66-BK

**Minimum Tensile Strength (Imperial)**

50.0

**Minimum Tensile Strength (Metric)**

225

**Length L (Imperial)**

9.0

**Length L (Metric)**

225

**Fixation Method**

Arrowhead

**Identification Plate Position**

none

**Releasable Closure**

Yes

**Width W (Imperial)**

0.2

**Width W (Metric)**

5.0

**Bundle Diameter Min (Imperial)**

0.24

**Bundle Diameter Min (Metric)**

6.0

**Bundle Diameter Max (Imperial)**

2.0

**Bundle Diameter Max (Metric)**

50.0

**Thickness T (Imperial)**

0.055

<b>Thickness T (Metric)</b>	1.4
<b>Height H (Imperial)</b>	0.24
<b>Height H (Metric)</b>	6
<b>Panel Thickness Min(Imperial)</b>	0.31
<b>Panel Thickness Max(Imperial)</b>	0.03
<b>Panel Thickness Min (Metric)</b>	0.8
<b>Panel Thickness Max (Metric)</b>	3.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.25 - 0.28
<b>Mounting Hole Diameter D (Metric)</b>	6.4 - 7.0 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.26
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.275
<b>Mounting Hole Diameter D Max (Metric)</b>	7.0
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)

<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	1.93