	m m		0	₿ >	
م	I		LAYOUT SHOWN AS EXAM	PLE	
	Keying Shown as example				
CHARACTERISTICS	Connector dimension	]			
-Standard : Based on MIL-DTL-38999 Series III	Dim         Nominal           ØS         41.7 Max				_
-Shell Material       : Aluminium         -Shell Plating       : Olive drab Cadmium         -Insulator       : Thermoplastic         -Contacts       : Copper Alloy	Z 31 Max VV THREAD M31x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)		
-Seals & Grommet : Silicon Elastomer			Country	Jurisdiction & Control List	
<ul> <li>-Contact Plating : Gold over copper Alloy 0.8μm minimum</li> <li>-Durability : 500 Mating cycles</li> </ul>			FR Not Listed		
-Delivered with Souriau contacts and Accessories			PN: 8D521W72PA		
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 10-10-201	6 First Release		
		ISS DATE	Latest modification - by		MOD N°
		Designed By:	Date:	CUSTOMER DRAWING	
		TITLE	TITLE Aluminium Plug 8D series		
	72 P A	SCALE	General linear Tolerances:	NPRDS / PROJECT <b>859</b>	
SHELL TYPE : Plug with RFI Shielding				This document is the prope	erty of
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21	CONTACT TYPE : PIN(5		SOURIAU WWW.SOURIAU.COM SOURIAU it must not be reproduced or communicated without permission		
PLATING : W = Olive drab Cadmium	CONTACT LAY		SOURIAU DI		SHEET
		A3	8D521W72		1/2

	Ŧ	۵	п –	m		0
		Contact louget				
		Contact Layout <b>72</b>				
		12				
4						
		2#4 Power				
	[	6#16 21-72	1			
	Ctc	X Y	-			
	Α	0 6.19	]			
	В	8.5 4.3				
	С	6.25 0	-			
ယ	D	8.5 -4.3				
	E F	0 -6.19 -8.5 -4.3	-			
	G	-6.25 0	-			
	Н	-8.5 4.3	]			
	I					
						SOURIAU shall not be liable for any
						due to a use of the Products wh
						the Specifications issued by either of (professional recommendat
						Countr
N						FR
						PN: 8D521V
						16 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumin
					SCALE	General linear Tolerances:
<u> </u>					NA	
					SOURIA	U WWW.SOURIAU.C
						SOURIAU
l		1 -		F	A3	8D521W
	Н	G	l F	E	D	C

