T G T	n m	D	0	B		]			
A			<image/> <section-header></section-header>	<image/>		4			
Ker CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	eying Shown as example Connector dimension Dim Nominal								
-Shell Material: Aluminium-Shell Plating: Black Zinc Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer	A         38.1±0.3           B         23.82+0.1/-0.15           R         32.5Max           S         34.9±0.4           W         2.2+0.9/-0.1           VV THREAD         M18x1-6g		SOURIAU shall not be liable for any n due to a use of the Products which the Specifications issued by either of th (professional recommendation Country	n does not comply with ne Parties or by a third party n, technical notice.) Jurisdiction & Control List		2			
<ul> <li>Contact Plating : Gold over copper Alloy 0.8μm minimum</li> <li>Durability : 500 Mating cycles</li> <li>Delivered without Souriau contacts</li> </ul>	FR       Not Listed         -Durability       : 500 Mating cycles								
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 29-09-202 ISS DATE	16 First Release Latest modification - by		MOD N°	-			
		Designed By:	Date:	CUSTOMER DRAWING					
		TITLE	Aluminium F	Receptacle 8D series					
BASIC SERIES:     8D     7     -     13     Z     04            → SHELL TYPE : Jam nut Receptacle	P B L Delivered W/O Conta	acts NA	General linear Tolerances: ±	NPRDS / PROJECT 859 This document is the pro	perty of	1			
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13	ORIENTATION CONTACT TYPE : PIN(500 Matin		U WWW.SOURIAU.CO	COLIDIALI	ced or				
PLATING : Z = Black Zinc Nickel	CONTACT LAYOUT : 13		SOURIAU E 8D713Z04	DRG N°	SHEET				
H G F	Ε	D	C	B A					

Г	D L	П	Ш	D	0	Φ	A		n
4	Contact Layout $ ^{\bullet, + \vee}_{-\times} ^{\bullet, \bullet}_{\oplus} ^{\bullet, \bullet}_{\bullet} ^{\bullet, \bullet}_{\bullet}$			I MAL	Panel cutout	A			4
	Contacts (Insert arrangement 13-4)           Contact         Location           Contact         X-axis           position ID         (mm)           A         +.000 (0.00)           B         +.146 (3.71)           C         +.000 (0.00)           C         +.000 (0.00)           C         +.000 (0.00)          146 (3.71)         +.035 (0.89)           Shell         Arrangement				ØC	rcn ₩			
ى س	size     no.     contacts     rating     location       13     -4     4     16     I     All     MS20051-4				Dim         Nominal           B         24.26+0/-0.2           ØC         25.65+0.25/-				3
				t	SOURIAU shall not be liable due to a use of the Proc he Specifications issued by e	lucts which does not co	mply with y a third party		
2					-		ction & Control List Not Listed		2
				A 29-09-2016 First ISS DATE L Designed By:	st Release atest modification - by Date:		CUSTOMER DRAWING	MOD N°	-
<u> </u>				SCALE NA	General Toleral ±-	nces: -	e 8D series NPRDS / PROJECT 859 This document is the prop SOURIAU	erty of	1
	HG	F	E	FORMAT A3		AU.COM RIAU DRG N° 13Z04PBL-C B	SOURIAU it must not be reproduce communicated without per		
		F I			U	D	I A		