

THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER. .X ±0.25

.XX ±0.13 .XXX ±0.05










## NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ" GOLD PLATED



POWER/CO-AX CONTACT RATING:	50Ω (IMPEDANCE)
(IF PRESENT)	
SIGNAL CONTACT CURRENT RATING:	5A PER CONTACT
SIGNAL CONTACT RESISTANCE:	10mΩ MAX.
	5000MO min


INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:

**OPERATING TEMPERATURE:** 


5000MΩ min.

-55°C ~ 125°C

1000V AC rms



				SW REFERENCE NO.: 629 COMBO ASSEMBLY							
		COMBINATION D-SUB			DRAWN: C.B			DATE: JAN. 01/2019			
				CHECKED:			DATE:				
	EDAC	CANADA	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE:	(IN C.A.D. 1:	1)	SHEET	1	OF	2	
				DRAWING NUMBER: 629-13W3			3640-5N4			ISSUE	
YOUR CONNECTION 1	OUR CONNECTION TO			PART NUN	/IBER:	629-13W3	3640-5N4	Ļ		1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

COMPLIANT

