

**APP ITB 2.5 BB 2C/NDT BL****Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

**Building installation wiring**

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Version    | A-series, End plate        |
| Order No.  | <a href="#">2668870000</a> |
| Type       | APP ITB 2.5 BB 2C/NDT BL   |
| GTIN (EAN) | 4064675030461              |
| Qty.       | 20 pc(s).                  |

## APP ITB 2.5 BB 2C/NDT BL

Weidmüller Interfaces GmbH &amp; Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

[info@weidmueller.com](mailto:info@weidmueller.com)

## Technical data

[www.weidmueller.com](http://www.weidmueller.com)

1.934 inch

2.823 inch

0.118 inch

## Temperatures

Storage temperature -25 °C...55 °C

Continuous operating temp., max. 130 °C

Continuous operating temp., min. -60 °C

## Material data

Material Wemid

UL 94 flammability rating V-0

Colour blue

## System specifications

Version End and intermediate plate

## Additional technical data

Snap-on Yes

## Classifications

ETIM 6.0 EC000886

ETIM 8.0 EC000886

ECLASS 9.1 27-14-11-33

ECLASS 11.0 27-14-11-92

ETIM 7.0 EC000886

ECLASS 9.0 27-14-11-92

ECLASS 10.0 27-14-11-92

ECLASS 12.0 27-14-11-92

## Downloads

Engineering Data [CAD data – STEP](#)Catalogues [Catalogues in PDF-format](#)

|            |          |
|------------|----------|
| Depth      | 49.13 mm |
| Height     | 71.7 mm  |
| Width      | 3 mm     |
| Net weight | 3.87 g   |

|                 |            |
|-----------------|------------|
| Depth (inches)  | 1.934 inch |
| Height (inches) | 2.823 inch |
| Width (inches)  | 0.118 inch |

|                                  |                |
|----------------------------------|----------------|
| Storage temperature              | -25 °C...55 °C |
| Continuous operating temp., max. | 130 °C         |

|                                  |        |
|----------------------------------|--------|
| Continuous operating temp., min. | -60 °C |
|----------------------------------|--------|

|                           |       |
|---------------------------|-------|
| Material                  | Wemid |
| UL 94 flammability rating | V-0   |

|        |      |
|--------|------|
| Colour | blue |
|--------|------|

|         |                            |
|---------|----------------------------|
| Version | End and intermediate plate |
|---------|----------------------------|

|         |     |
|---------|-----|
| Snap-on | Yes |
|---------|-----|

|             |             |
|-------------|-------------|
| ETIM 6.0    | EC000886    |
| ETIM 8.0    | EC000886    |
| ECLASS 9.1  | 27-14-11-33 |
| ECLASS 11.0 | 27-14-11-92 |

|             |             |
|-------------|-------------|
| ETIM 7.0    | EC000886    |
| ECLASS 9.0  | 27-14-11-92 |
| ECLASS 10.0 | 27-14-11-92 |
| ECLASS 12.0 | 27-14-11-92 |

|                  |  |
|------------------|--|
| Engineering Data | <a href="#">CAD data – STEP</a>          |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |