


a YAGEO company

C1825Q334K5XAH

GR900 SMD Space, Ceramic, 0.33 uF, 10%, 50 VDC, BX, N/A, 1825



Click here for the 3D model.

Dimensions	
Chip Size	1825
L	4.57mm +/-0.38mm (0.18 in +/-0.015 in)
W	6.35mm +/-0.38mm (0.25 in +/-0.015 in)
Т	2.03mm MAX (0.08 in MAX)
В	0.51mm +/-0.25mm (0.02 in +/-0.01 in)

Packaging Specifications	
Packaging	Bulk, Bag

GR900 SMD Space
SMD Chip
No
▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.
4848e250-8508-4d7b-8b2c-b2000a1148f1
Lead (SnPb)
N/A
Mil-PRF-123 Group A
MIL-PRF-123 Group A
No
78 Weeks
1

Specifications	
Capacitance	0.33 uF
Capacitance Tolerance	10%
Voltage DC	50 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	BX

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.