



25-PIN MALE DSUB ASSEMBLY  
METAL SHELL AND #4-40 JACKSCREWS  
BOTH ENDS  
(SEE NOTE 2)

DB25 TO DB25 YAMAHA WIRING CHART (BOTH ENDS)				
(PAIR)	(CABLE)	(RED)	(BLACK)	(BARE)
1	BROWN	5	18	24
2	RED	6	19	12
3	ORANGE	7	20	25
4	YELLOW	8	21	13
5	GREEN	1	14	22
6	BLUE	2	15	22
7	PURPLE	3	16	23
8	GRAY	4	17	10
PINS 9 & 11 NO CONNECTION				

PART NUMBER	CABLE LENGTH "X"
DB25M05DB25MY	5.00 FT +/- 1.50 IN
DB25M10DB25MY	10.00 FT +/- 1.50 IN

**CUSTOMER DRAWING**

B

**NOTES:**

1. THE PRODUCT COMES COILED AND PACKAGED IN A BAG.
2. JACKSCREWS ARE SHIPPED UNASSEMBLED. CABLE COMES WITH BOTH #4-40 THREAD (4) AND #M3 THREAD (4) JACKSCREWS.
3. MATERIALS:  
DSUB - COPPER ALLOY, NICKEL PLATED WITH GOLD PINS  
CABLE - COPPER, THERMOPLASTIC  
JACKSCREWS - STAINLESS STEEL
4. THIS PRODUCT IS RoHS COMPLIANT.

REV	ECO NUMBER	DATE	BY	APVD
B	26637	10/4/10	RS	TJK
A	26569	7/20/10	RS	TJK
REVISIONS				

UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS IN INCHES  
- TWO PLACE DECIMALS ±0.02  
- THREE PLACE DECIMALS ±0.005

DO NOT SCALE DRAWING

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.									
SIZE	WIDTH	MULT	LBS/M	TEMPER					
FINISH					MATERIAL				
SPEC No.					SPEC No.				
FIRST USED ON					SCALE				
					1:1				
DATE DRAWN	BY	CHKD	APVD						
10/23/09	JGK	RS	TJK						
		8/12/10	1/21/11						
NAME				PART No.				REV	
DB25M TO DB25M, YAMAHA, RoHS				DB25M__DB25MY				B	
SHEET 1 OF 1									

SolidWorks CAD File B