




| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 46.7              |
| B1  | 21.5              |
| B2  | 16.6              |
| C   | 24.05             |
| D   | 4                 |
| E   | 79                |
| F   | 50.9              |
| G   | 47.6              |

| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|---|
| 2   | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 3   | DICHTKÖRPER / GROMMET                   |
| 4   | ENDRING / ENDRING                       |
| 6   | KONTAKTBUCHSE / CONTACT SOCKET          |
| 8   | DOSENGEHÄUSE / SHELL                    |
| 12  | ENDGEHÄUSE / ENDBELL                    |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

|  |
|--|
| <b>Material Specification:</b>                 |
| Shell Material: Aluminium alloy                |
| Shell Plating: Zinc cobalt, black (conductive) |
| Insulator Material: CR-Elastomere              |
| Contact Material: Copper alloy                 |
| Contact Plating: Hard silver                   |

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m  
 drawing for CUSTOMER

**ITT**  
*Engineered for life*  
 ITT CANNON GmbH  
 D - 71384 Weinstadt/Germany

description CA3101E28A63S-B-F80-A232  
 Cable connecting plug  
 Endbell with clamp and bushing  
 AWG Crimp / Socket / Layout: 28A63