





Rev	AWO #	Description	Date	Appr
-		RELEASED	1/14/09	

APPROVED: _____
 DATE: _____ TITLE: _____



SPECIFICATIONS:

- Material: Nylon 66, rated UL 94V-0
- Insulator color: White
- Contacts: Brass
- Plating: Tin over Copper underplate overall
- Electrical:
 - Operating voltage: 250 VAC max
 - Current rating: 7 Amps max
 - Contact resistance: 20 mohms max
 - Insulation resistance: 1,000 Mohms min
 - Dielectric withstanding voltage: 1,500 VAC for 1 minute
- Temperature Rating:
 - Operating temperature: -25°C to +85°C
- Environmental: Lead free, RoHS compliant

Positions: 2 thru 12
 A = .156 [3.96] x No. of Positions
 B = .156 [3.96] x No. of Spaces

ADAM TECH

909 Railway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

TITLE: .156 [3.96] POWER HEADER
 STRAIGHT, WITH REAR LOCK

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]	
TOLERANCES: EXCEPT AS NOTED	
INCHES	HOLE
.X ± .10	ØX ± .10
.XX ± .020	ØXXX ± .015
.XXX ± .015	ØXXX ± .010
APPROVALS	DATE
DRAWN	SS
CHECKED	
APPROVED	

SIZE	PART NO.	REV.
X	LHC-XX-TS-V0	-
REF:	SCALE: NTS	SHEET 1 OF 1

