



### Main

Range	Spacial
Extended range	Spacial SF
Application	PC application
Product or Component Type	Suitable enclosure
Enclosure nominal height	62.99 in (1600 mm)
Enclosure nominal width	23.62 in (600 mm)
Enclosure nominal depth	31.50 in (800 mm)
Enclosure mounting	Floor-standing
Product Specific Application	Protecting computer equipment
Device composition	1 structure 1 roof 2 side panels 1 cable gland plate 1 partial door for keyboard 1 partial door for PC screen 1 partial door for printer support 1 rear door

### Complementary

Structure type	Perforated structure with a pitch of 25 mm Vertical uprights joined with top and bottom frames Formed from a single section Panels and doors built into the structure
Door type	Plain partial front Glazed partial front Solid rear
Number of doors	Front 3 Rear 1
Door opening side	Reversible 120 °)
Lock type	Flat escutcheon lock, 5 mm double bar rear door Escutcheon lock, 3 mm double bar front partial doors
Mounting plate description	Without mounting plate
Type of gland plate	Standard
Cable entry	1 entry
Number of compartments	3
Accessibility for operation	Rear Sides of enclosure Front
Removable parts	Roof by screws internally Side panel by screws internally Door by screws hinge
Material	Frame galvanised steel Uprights galvanised steel Door sheet steel Panels sheet steel Hinge zamak Escutcheon polyamide 6 with 30 % fibre glass
Surface finish	Epoxy-polyester powder
Color	Enclosure Gray RAL 7035) Handle Black RAL 9005)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Standards	IEC 62208
IP degree of protection	IP55 IEC 60529
IK degree of protection	IK08 IEC 62262 of transparent door) IK10 IEC 62262 of plain door)

## Ordering and shipping details

Category	80035-ENCLOSURE SYSTEMS FLOOR MOUNT
Discount Schedule	ES1
GTIN	3606485118758
Nbr. of units in pkg.	1
Package weight(Lbs)	222.01 lb(US) (100.7 kg)
Returnability	No
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	25.59 in (65.0 cm)
Package 1 width	35.04 in (89.0 cm)
Package 1 Length	83.86 in (213.0 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------