REVISION S

DO NOT

CALE FROM THIS PRINT

DESIGNED AND DIMENSIONED IN MILLIMETERS[INCHES] ALL DIMENSIONS REFERENCE EXCEPT AS SHOWN

P6) THIS PRODUCT MANUFACTURED WITH LEAD-FREE PROCESSING

CABLE CALLOUT

047-A: CCA-047-PFA CABLE

END 1 CONNECTOR-(SEE TABLE 2, SHT 2) OVERALL ASSEMBLY LENGTH (OAL) XXXX (MILLIMETERS) (0100 MIN)

END 2 CONNECTOR (SEE TABLE 2, SHT 2)





FIG 1 RF047-A-M0SJ-M0SP-XXXX SHOWN (PROTECTIVE CAPS NOT SHOWN FOR CLARITY)

TABLE 1					
OVERALL LENGTH	"G"				
0100-0300 [5.98-11.81]	+5.0 [.20] / -0.0 [.00]				
0301-1500 [11.85-59.01]	+12.0 [.47] / -0.0 [.00]				
1501-3000 [59.09-118.11]	+25.0 [.98] / -0.0 [.00]				
3001-7500 [118.15-295.28]	+50.0 [1.97] / -0.0 [.00]				
7501-9999 [295.31-393.67]	+1% / -0.0 [.00]				



NOTES:

- 1. NOTE DELETED.
- 2. NOTE DELETED.
- 3. CONNECTORS TO BE ORIENTED ACCORDING TO CO-RF-WI-3048-M.
- 4. CABLE ASSEMBLY TO HAVE PROTECTIVE CAPS ASSEMBLED ON EACH END AND INDIVIDUALLY PACKAGED IN ESD BAG.
- 5. ASSEMBLY TO BE 100% TESTED FOR RETURN LOSS AND INSERTION LOSS. LABEL EACH INDIVIDUAL CABLE ASSEMBLY WITH 1 LABEL-SER-02. RETURN LOSS SPECIFICATION IS EQUAL TO THE HIGHEST END OPTION LIMIT.
- 6. CABLE LENGTHS LONGER THAN 1000 MILLIMETERS ARE NOT SUPPORTED BY S.I. TEST DATA.
- 7. DIM "H", "J", AND "K" HAVE A MINIMUM VALUE OF 0.0mm & A MAXIMUM VALUE OF 9.9mm[.39"]
- 8. FOR STRIPPED AND TINNED OPTION, BOTH THE CENTER CONDUCTOR IS TINNED.

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE

OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC.

CENTER CONTACTS: COPPER ALLOY SHEET SCALE: 3:1 OUT CONTACTS:

-MOSP/-MOS I/MOR I/-MOR I/-O1SP/-O18 I/-O1SR/-OOS I/-OOM I: COPPER ALLOY

-92SP/-92SJ/-18SP/-18SJ/-24SP/-24SJ/ -13BJ/-13SP: STAINLESS STEEL INSULATORS:

NOGE/HONGS./-MOBJ/-MOBJ/-01SP/-01BJ/-01SB/-00SJ/-00MJ: VIRGIN PTFE FLUOROCARBON -92SP/-92SJ/-18SJ/-18SJ/-24SP/-24SJ: ULTEM -13BJ/-13SP: PCTFE -13BJ: VIRGIN PTFE -00SJ/-00MJ:PEER



520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com

DO NOT SCALE DRAWING DESCRIPTION

RF047-A CABLE ASSEMBLY

BY: SHERRY W 2/5/2018 SHEET 1 OF 12

F:\DWG\MISC\Mktg\RF047-A-XXXX-XXXXXXXXXX-MKT.SLDDRW

REVISION S

TABLE 2								
END		GENDER	FINISH					
OPTION	SERIES		CENTER CONTACT	OUTER CONTACT	CABLE BODY	CONNECTOR KIT P/N	FIGURE	
-M0SP	SMPM	PLUG FULL DETENT	30μ" GOLD	10μ" GOLD	3μ" GOLD	PRFM0-P-C-HG-047A-SD	SHT 3, FIG 2	
-M0SJ	SMPM	JACK	30µ" GOLD	10μ" GOLD	3μ" GOLD	PRFM0-J-C-HG-047A-SD	SHT 3, FIG 3	
-92SP	2.92 MM	PLUG	50μ" GOLD	PASSIVATED	PASSIVATED	PRF92-P-C-EP-047A-SS	SHT 4, FIG 4	
-92SJ	2.92 MM	JACK	50μ" GOLD	PASSIVATED	PASSIVATED	PRF92-J-C-EP-047A-SS	SHT 4, FIG 5	
-18SP	1.85 MM	PLUG	50μ" GOLD	PASSIVATED	PASSIVATED	PRF18-P-C-EP-047A-SS	SHT 5, FIG 6	
-18SJ	1.85 MM	JACK	50μ" GOLD	PASSIVATED	PASSIVATED	PRF18-J-C-EP-047A-SS	SHT 5, FIG 7	
-24SP	2.4 MM	PLUG	50μ" GOLD	PASSIVATED	PASSIVATED	PRF24-P-C-EP-047A-SS	SHT 6, FIG 9	
-24SJ	2.4 MM	JACK	50μ" GOLD	PASSIVATED	PASSIVATED	PRF24-J-C-EP-047A-SS	SHT 6, FIG 10	
-M0RJ	SMPM	RIGHT ANGLE JACK	50μ" GOLD	50μ" GOLD	50μ" GOLD	PRFM0-J-C-EE-047A-RD	SHT 7, FIG 11	
-M0BJ	SMPM	BULKHEAD JACK	50μ" GOLD	50μ" GOLD	50μ" GOLD	PRFM0-J-C-EE-047A-BD	SHT 7, FIG 12	
-13SP	1.35 MM	PLUG	50μ" GOLD	PASSIVATED	PASSIVATED	PRF13-P-C-VP-047A-SS	SHT 8, FIG 13	
-13BJ	1.35 MM	JACK	50μ" GOLD	PASSIVATED	PASSIVATED	PRF13-J-C-VP-047A-BS	SHT 8, FIG 14	
-GC47	SMPM	JACK	50μ" GOLD	PASSIVATED	PASSIVATED	PRFM0-J-C-EE-047A-SD-1	SHT 9, FIG 15	
*-10SP	1.0 MM	PLUG	50μ" GOLD	PASSIVATED	PASSIVATED	PRF10-P-C-VP-047A-SS-X	SHT 9, FIG 16	
*-10BJ	1.0 MM	JACK	50μ" GOLD	PASSIVATED	PASSIVATED	PRF10-J-C-VP-047A-BS-X	SHT 10, FIG 1	
*-01SP	SMA	PLUG	50μ" GOLD	10μ" GOLD	10μ" GOLD	PRF01-P-C-EG-047A-SD	SHT 10, FIG 1	
*-01BJ	SMA	BULKHEAD JACK	50μ" GOLD	10μ" GOLD	10μ" GOLD	PRF01-J-C-EG-047A-BD	SHT 11, FIG 1	
*-01SB	SMA	SEALED BULKHEAD JACK	50μ" GOLD	10µ" GOLD	10μ" GOLD	PRF01-J-C-EG-047A-BD-1	SHT 11, FIG 2	
*-00SJ	SMP	JACK	50µ" GOLD	50µ" GOLD	50µ" GOLD	PRF00-J-C-EE-047A-SD-X	SHT 12, FIG 2	
*-00MJ	SMP	R/A JACK	50μ" GOLD	50μ" GOLD	50μ" GOLD	PRF00-J-C-EE-047A-RD-1-X	SHT 12, FIG 2	
**-SING	SINGLE ENDED STRIPPED & TINNED	-	-	-	-	-	-	

^{* =} NOT RELEASED

TABLE 3									
		MAXIMUM RETURN LOSS	MAXIMUM INSERTION LOSS (IL)	FREQUENCY	PROTECTIVE CAP COLOR				
-MOSP	1.40:1	-15.56 dB	0.28	DC TO 40 GHz	GRAY				
-M0SJ	1.40:1	-15.56 dB	0.28	DC TO 40 GHz	GRAY				
-92SP	1.35:1	-16.45 dB	0.28	DC TO 40 GHz	YELLOW				
-92SJ	1.35:1	-16.45 dB	0.28	DC TO 40 GHz	YELLOW				
-18SP	1.40:1	-15.56 dB	0.37	DC TO 67 GHz	BLUE				
-18SJ	1.40:1	-15.56 dB	0.37	DC TO 67 GHz	BLUE				
-24SP	1.35:1	-16.45 dB	0.32	DC TO 50 GHz	GREEN				
-24SJ	1.35:1	-16.45 dB	0.32	DC TO 50 GHz	GREEN				
-M0RJ	1.40:1	-15.56 dB	0.20	DC TO 20 GHz	N/A				
-M0BJ	1.40:1	-15.56 dB	0.28	DC TO 40 GHz	N/A				
-13SP	1.40:1	-15.56 dB	0.39	DC TO 90 GHz	GRAY				
-13BJ	1.40:1	-15.56 dB	0.39	DC TO 90 GHz	GRAY				
-GC47	1.40:1	-15.56 dB	0.28	DC TO 40 GHz	N/A				
*-10SP	1.40:1	-15.56 dB	0.4	DC TO 110 GHz	WHITE				
*-10BJ	1.40:1	-15.56 dB	0.4	DC TO 110 GHz	WHITE				
*-01SP	1.30:1	-17.7 dB	0.23	DC TO 26.5 GHz	BROWN				
*-01BJ	1.30:1	-17.7 dB	0.23	DC TO 26.5 GHz	BROWN				
*-01SB	1.30:1	-17.7 dB	0.23	DC TO 26.5 GHz	BROWN				
*-00SJ	1.20:1	20.83 dB	0.5	DC TO 26.5 GHz	WHITE				
	1.50:1	14.0 dB	0.5	26.5 GHz TO 40 GHz	VAC UTE				
*-00MJ	1.20:1	20.83 dB	0.5	DC TO 26.5 GHz	WHITE				

IL Max [dB] for cable assembly:

F:\DWG\MISC\Mktg\RF047-A-XXXX-XXXXXXXXXX-XXXX-MKT.SLDDRW

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS
AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC.

> DO NOT SCALE DRAWING SHEET SCALE: 4:1

520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322

DESCRIPTION:


RF047-A CABLE ASSEMBLY


RF047-A-XXXX-XXXXXXXXXXXXX


BY: SHERRY W


2/5/2018 SHEET 2 OF 12


^{= {35.06*}SQRT(Freq[GHz])+1.835*Freq[GHz]}*OAL[mm]/30480+End Option IL#1{See Table 3}+End Option IL#2{See Table 3}
*= NOT RELEASED














F:\DWG\MISC\Mktg\RF047-A-XXXX-XXXXXX-XXXX-MKT.SLDDRW

* PROPRIETARY NOTE THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, USE, PATENT RIGH AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMT

PROPRIETARY INFORMATION AND ALL DESIGN.

AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTER,

AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTER,

INC. THIS DOCUMENT SHALL NOT BE OSICLOSED, IN WHOLE

OR PART, TO ANY UNALITHORIZED PERSON OR ENTITY NOR

REPRODUCED, TRANSFERRED OR HOROPROFILED IN ANY

OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS

WRITTEN CONSENT OF SAMTER, LINE

SHEET SCALE: 4:1




520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322


DESCRIPTION:

RF047-A CABLE ASSEMBLY

WG NO

BY: SHERRY W 2/5/2018 SHEET 7 OF 12






F:\DWG\MISC\Mktg\RF047-A-XXXX-XXXXXXXXXX-MKT.SLDDRW


SHEET SCALE: 4:1


RF047-A CABLE ASSEMBLY

DWG. NO. RF047-A-XXXX-XXXXXXXXXXXXXX BY: SHERRY W

2/5/2018 SHEET 9 OF 12







REVISION S

FIG 21 -015J SHOWN (PROTECTIVE CAP NOT SHOWN FOR CLARITY)

