TRIPP-LITE

USB-C Multiport Adapter, 2x USB-A and 1X USB-C Ports, Card Reader, USB 3.0, Silver

MODEL NUMBER: U460-002-2AM-C1





Adds USB-A and USB-C ports and memory card slots to the USB-C or Thunderbolt 3 port on your MacBook, Chromebook, tablet or notebook.

Features

USB-C/Thunderbolt 3 Hub Connects USB Peripherals to Your Laptop or TabletThis USB-C hub allows you to connect up to three USB peripherals to your tablet, laptop, notebook, MacBook, Chromebook, smartphone or PC. This lets you expand the potential of your device by connecting USB peripherals, such as an external hard drives, flash drives, power meters and printers.

USB Ports Transfer Data from Peripheral to Device at Fast USB 3.1 Gen 1 SpeedsBoth USB-A ports and the USB-C port transfers data at speeds up to 5 Gbps, which is 10 times faster than USB 2.0. The USB ports are backward compatible with previous USB generations, so you can continue using older peripherals while getting high-speed performance from new devices.Note: Host must support USB OTG (On-the-Go)Dual Memory Card Slots Are Ideal for Moving Large Files

You can also insert memory cards into their corresponding slots to transfer data at USB 2.0 speeds up to 480 Mbps. The memory card readers support MicroSD and SD/MMC cards for convenient access to digital photos, camcorder videos, smartphone data and other essential files. Both memory card slots can be used simultaneously for maximum access to external storage.

Built-In USB-C Cable Connects in Either DirectionConnect the reversible USB-C plug to your source device's USB-C or Thunderbolt 3 port. The fumble-free USB-C plug connects in either direction to ensure fast, easy connection every time.

Ready to Use Right Out of the PackageThe plug-and-play USB Type-C hub is specifically designed for use with the MacBook, Google Chromebook Pixel and other laptops, tablets and devices equipped with a USB-C or Thunderbolt 3 port. It requires no software, drivers or external power. The aluminum housing is about the size of a credit card to make it easy to carry in a pocket, backpack or laptop bag for use anywhere.

Specifications

OVERVIEW

Highlights

- USB-C 3.1 hub is compatible with all USB-C and Thunderbolt 3 devices
- Connects external hard drives, keyboard, printer and other USB peripherals
- Supports USB 3.1 Gen 1 speeds up to 5 Gbps to ensure fast data transfers
- Reversible USB-C plug connects in either direction for immediate no-fuss use
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Connect up to 3 USB peripherals, such as an external hard drive, flash drive and keyboard/mouse
- Transfer photos, videos and other important files between your MacBook or Chromebook and a memory card

System Requirements

• Device with USB-C or Thunderbolt 3 port (USB 3.1 port needed to achieve USB 3.1 speeds)

Package Includes

- U460-002-2AM-C1 USB 3.1 Gen 1 USB-C Portable Hub/Adapter
- Owner's manual

TRIPP-LITE

Product Type Multiport Adapter Host Connector USB C (MALE) viceo Number of Monitors Supported 1 Extended Mode No Miror Mode No Data No Data Forts (2) USB A (FEMALE): USB C (FEMALE) Data Ports Details (2) USB A (FEMALE): USB C (FEMALE) Data Ports Details (2) USB A - USB 3.2 Gen 1 (6 Obps): USB-C - USB 3.2 Gen 1 (6 Obps) STORAGE Card Slots SD (FEMALE): MICRO SD (FEMALE) Card Slots Details SD 5.0 Memory Card slots (SD and MicroSD) - both can be used simultaneously Strone INPUT SD 1 Built-In Cable Longth (n.) SD 1 SD FEMALE): MICRO SD (FEMALE) SD 1 Built-In Cable Longth (n.) 1.3 Product Longth (n.) 0.372 Product Longth (n.) 0.372 Product Longth (n.) 0.372			
Heat Connector USB C (MALE) veeo I Number of Monitors Supported I Extended Mode No Marror Mode No Data Ports I Data Ports (2) USB A (FEMALE): USB C (FEMALE) Data Ports (2) USB - VISB 3.2 Gen 1 (S Gbps): USB-C - USB 3.2 Gen 1 (S Gbps) STORAGE Storewall Card Stots SD (FEMALE): MICRO SD (FEMALE) Card Stots Datalis SD 70 Morrory Card stots (SD and MicroSD) - both can be used simultaneously Storewall SD 10 Morrory Card stots (SD and MicroSD) - both can be used simultaneously Stots Datalis SD 10 Morrory Card stots (SD and MicroSD) - both can be used simultaneously Storewall Sufficience (SD 10, SD 1	UPC Code	037332218353	
VIDEO Number of Monitors Supported 1 Extended Mode No Mirror Mode No Data No Data Ports (2) USB A (FEMALE); USB C (FEMALE) Data Ports (2) USB A (FEMALE); USB C (FEMALE) Data Ports Details (2) USB A (FEMALE); USB C (FEMALE) Store Porte (2) USB A (FEMALE); USC O SD (FEMALE) Card Store (2) USB A (FEMALE); MICRO SD (FEMALE) Card Store Details SD 3 0 Memory Card store (SD and MicroSD) - both can be used simultaneously INPUT Sole SD 3 0 Memory Card store (SD and MicroSD) - both can be used simultaneously Sult-In Cable Length (m.) 5.91 Built-In Cable Length (m.) 5.91 Built-In Cable Length (m.) 5.91 Built-In Cable Length (m.) 4.49 Product Length (m.) 0.372 Product Length (m.) 0.113 Battery Charging (SV/1.5A Port) No USER INTERFACE, ALERTS & CONTROL Super Lib Indicators White (Connection) Physiccal Connection) Physiccal Sit/er			
Number of Monitors Supported 1 Extended Mode No Mirror Mode No Data Onco Data Onco Data Ports (2) USB A (FEMALE); USB C (FEMALE) Data Ports Details (2) USB A, - USB 3.2 Gen 1 (5 Gbps); USB-C - USB 3.2 Gen 1 (5 Gbps) STORAGE StorAGE Card Slots SD (FEMALE); MICRO SD (FEMALE) Card Slots Details SD 3.0 Memory Card slots (SD and MicroSD) - both can be used simultaneously INPUT Built-In Cable Length (m.) S.91 Sub Scheele Simultaneously INPUT Built-In Cable Length (m.) S.91 Deduct	Host Connector	USB C (MALE)	
Extended Mode No Mirror Mode No Data Onto Data Ports (2) USB A (FEMALE); USB C (FEMALE) Data Ports Details (2) USB A - USB 3.2 Gen 1 (6 Gbps); USB-C - USB 3.2 Gen 1 (6 Gbps) StorAGE StorAGE Card Slots SD (FEMALE); MICRO SD (FEMALE) Card Slots Details SD 3.0 Memory Card slots (SD and MicroSD) - both can be used simultaneously INPUT Built-In Cable Length (m.) 5.91 Built-In Cable Length (m.) 1.5 Bus Powered Yes Product Length (m.) 1.135 Product Length (m.) 0.372 Product Length (m.) 0.113 Battery No USER INTERFACE, ALERTS & COUNCED Silver LeD Indicators White (Connection) PhysicaL Silver Calor Silver Material of Construction Auminum Cable Jacket Material </td <td>VIDEO</td> <td></td>	VIDEO		
Miror Mode No Data Data <t< td=""><td>Number of Monitors Supported</td><td>1</td></t<>	Number of Monitors Supported	1	
DATA Data Ports (2) USB A (FEMALE); USB C (FEMALE) Data Ports Details (2) USB A - USB 3.2 Gen 1 (5 Gbps); USB-C - USB 3.2 Gen 1 (6 Gbps) STORAGE Card Slots SD (FEMALE); MICRO SD (FEMALE) Card Slots Details SD 3.0 Memory Card slots (SD and MicroSD) - both can be used simultaneously INPUT Built-In Cable Length (In.) S.91 Droduct Length (In.) 4.49 Product Length (In.) 0.372 Product Length (In.) 0.113 Battery Charging (SV/1.5A Port) No USER INTERFACE, ALERTS & CONTEX LED Indicators White (Connection) PHYSICAL Silver Color Silver Material of Construction Auminum Cable Lacket Material PVC Cable Duter Diameter (OD) 4.5+0.15 mm	Extended Mode	No	
Data Ports (2) USB A (FEMALE); USB C (FEMALE) Data Ports Details (2) USB-A - USB 3.2 Gen 1 (5 Gbps); USB-C - USB 3.2 Gen 1 (5 Gbps) STORAGE Card Slots SD (FEMALE); MICRO SD (FEMALE) Card Slots Details SD 3.0 Memory Card slots (SD and MicroSD) - both can be used simultaneously INPUT Built-In Cable Length (in.) 5.91 Built-In Cable Length (cm.) 15 Built-In Cable Length (cm.) 4.49 Product Length (m.) 0.372 Product Length (m.) 0.372 Product Length (m.) 0.372 Product Length (m.) 0.40 Network USER INTERFACE, ALERTS & COMMENT Vertication No Silver Color Silver Color Silver Color Silver Color Silver Color PVC	Mirror Mode	No	
Data Ports Details C2U USB-A - USB 3.2 Gen 1 (5 Gbps); USB-C - USB 3.2 Gen 1 (6 Gbps) STORAGE StorAGE Card Slots SD (FEMALE); MICRO SD (FEMALE) Card Slots Details SD 3.0 Memory Card slots (SD and MicroSD) - both can be used simultaneously INPUT StorAGE Built-In Cable Length (in.) 5.91 Built-In Cable Length (in.) 5.91 Built-In Cable Length (in.) 15 Built-In Cable Length (in.) 0.91 Product Length (in.) 0.91 Built-In Cable Length (in.) 0.91 Product Length (in.) 0.91 Product Length (in.) 0.91 Details 0.372 Product Length (m.) 0.113 Battery Charging (SV/1.5A Port) No USER INTERFACE, ALERTS & COVERTIES StorAction PhysicaL Oliconection) Milte (Connection) PhysicaL Silver Silver Cable Jacket Material PVC Cable Jacket Material PVC Cable Jouket Tolameter (OD) 4.5 +/- 0.15 mm Material Cable Jacket Material PVC	DATA		
STORAGE Card Slots SD (FEMALE); MICRO SD (FEMALE) Card Slots Details SD 3.0 Memory Card slots (SD and MicroSD) - both can be used simultaneously INPUT Built-In Cable Length (in.) Built-In Cable Length (in.) 5.91 Built-In Cable Length (in.) 5.91 Built-In Cable Length (in.) 15 Built-In Cable Length (in.) 4.49 Product Length (in.) 4.49 Product Length (in.) 0.372 Product Length (in.) 0.113 BATERY Battery Charging (5V/1.5A Port) No USER INTERFACE, ALERTS & CONTENDIS LED Indicators White (Connection) PHYSICAL Color Color Silver Material of Construction Aluminum Cable Jacket Material PVC Cable Jourder (OD) 4.5 +/- 0.15 mm	Data Ports	(2) USB A (FEMALE); USB C (FEMALE)	
Card Slots SD (FEMALE); MICRO SD (FEMALE) Card Slots Details SD 3.0 Memory Card slots (SD and MicroSD) - both can be used simultaneously INPUT Intervention SD (FEMALE) Built-In Cable Length (in.) S.9.1 Built-In Cable Length (cm) I.5 Built-In Cable Length (cm) 15 Built-In Cable Length (cm) 4.49 Product Length (cm.) 11.35 Product Length (cm.) 0.372 Product Length (m.) 0.372 Product Length (cm.) 0.113 Battery Charging (SV/1.5A Port) No USER INTERFACE, ALERTS & COURCION White (Connection) PhysicaL Color Silver Color Silver Aluminum Cable Jacket Material PVC Color Gabe Jacket Material PVC Color Material Cource (CD)	Data Ports Details	(2) USB-A - USB 3.2 Gen 1 (5 Gbps); USB-C - USB 3.2 Gen 1 (5 Gbps)	
Card Slots Details SD 3.0 Memory Card slots (SD and MicroSD) - both can be used simultaneously INPUT INPUT Built-In Cable Length (in.) 5.91 Built-In Cable Length (cm) 15 Built-In Cable Length (cm) 15 Built-In Cable Length (in.) 4.49 Product Length (cm.) 11.35 Product Length (cm.) 0.372 Product Length (m.) 0.113 Battery Ohr (Connection) Battery Charging (5V/1.5A Port) No USER INTERFACE, ALERTS & COVTUS Vertice Connection) PHYSICAL Silver Color Silver Material of Construction Aluminum Cable Jacket Material PVC Cable Outer Diameter (OD) 4.5+/- 0.15 mm	STORAGE		
INPUT Built-In Cable Length (in.) 5.91 Built-In Cable Length (cm) 15 Built-In Cable Length (cm) 15 Bus Powered Yes Product Length (in.) 4.49 Product Length (cm.) 11.35 Product Length (ft.) 0.372 Product Length (m.) 0.113 BATTERY Battery Charging (5V/1.5A Port) No Vister (Connection) PHYSICAL Viste (Connection) PHYSICAL Silver Color Silver Material of Construction Aluminum Cable Jacket Material PVC Cable Outer Diameter (OD) 4.5 +/- 0.15 mm	Card Slots	SD (FEMALE); MICRO SD (FEMALE)	
Built-In Cable Length (in.) 5.91 Built-In Cable Length (cm) 15 Bus Powered Yes Product Length (in.) 4.49 Product Length (cm.) 11.35 Product Length (m.) 0.372 Product Length (m.) 0.113 Battery Charging (5V/1.5A Port) No User INTERFACE, ALERTS & COUNCIDENT LED Indicators White (Connection) PhysicaL Silver Color Silver Material of Construction Aluminum Cable Jacket Material PVC Cable Outer Diameter (OD) 4.5 ±/- 0.15 mm	Card Slots Details	SD 3.0 Memory Card slots (SD and MicroSD) - both can be used simultaneously	
Built-In Cable Length (cm) 15 Bus Powered Yes Product Length (in.) 4.49 Product Length (cm.) 11.35 Product Length (th.) 0.372 Product Length (m.) 0.113 Battery 0.113 Battery Charging (5V/1.5A Port) No USER INTERFACE, ALERTS & CONT Vite (Connection) PhysicaL Vite (Connection) PhysicaL Silver Color Silver Material of Construction Aluminum Cable Jacket Material PVC Cable Jacket Material PVC	INPUT		
Bus Powered Yes Product Length (in.) 4.49 Product Length (cm.) 11.35 Product Length (ft.) 0.372 Product Length (m.) 0.113 BATTERY Battery Charging (5V/1.5A Port) No USER INTERFACE, ALERTS & CONTRICION PhysicaL Color Silver Material of Construction Aluminum Cable Jacket Material PVC Cable Outer Diameter (OD) 4.5 ±/- 0.15 mm	Built-In Cable Length (in.)	5.91	
Product Length (in.) 4.49 Product Length (cm.) 11.35 Product Length (ft.) 0.372 Product Length (m.) 0.113 BATTERY Battery Charging (5V/1.5A Port) No Vertex Secondary	Built-In Cable Length (cm)	15	
Product Length (cm.) 11.35 Product Length (ft.) 0.372 Product Length (m.) 0.113 BATTERY Battery Charging (5V/1.5A Port) No USER INTERFACE, ALERTS & CONTROLS LED Indicators White (Connection) PHYSICAL Color Silver Material of Construction Aluminum Cable Jacket Material PVC Cable Jacket Material PVC Cable Journe Tion 4.5 +/- 0.15 mm	Bus Powered	Yes	
Product Length (ft.) 0.372 Product Length (m.) 0.113 BATTERY Battery Charging (5V/1.5A Port) No USER INTERFACE, ALERTS & CONTROL LED Indicators White (Connection) PHYSICAL Color Silver Material of Construction Aluminum Cable Jacket Material PVC Cable Outer Diameter (OD) 4.5 +/- 0.15 mm	Product Length (in.)	4.49	
Product Length (m.) 0.113 BATTERY Battery Charging (5V/1.5A Port) No USER INTERFACE, ALERTS & CONTROLS LED Indicators White (Connection) PHYSICAL Color Silver Material of Construction Aluminum Cable Jacket Material PVC Cable Outer Diameter (OD) 4.5 +/- 0.15 mm	Product Length (cm.)	11.35	
BATTERY Battery Charging (5V/1.5A Port) No USER INTERFACE, ALERTS & CONTROLS LED Indicators White (Connection) PHYSICAL Color Silver Material of Construction Aluminum Cable Jacket Material PVC Cable Outer Diameter (OD) 4.5 +/- 0.15 mm	Product Length (ft.)	0.372	
Battery Charging (5V/1.5A Port) No USER INTERFACE, ALERTS & CONTOLS LED Indicators White (Connection) PHYSICAL Color Silver Material of Construction Aluminum Cable Jacket Material PVC Cable Outer Diameter (OD) 4.5 +/- 0.15 mm	Product Length (m.)	0.113	
USER INTERFACE, ALERTS & CONTROLS LED Indicators White (Connection) PHYSICAL Color Silver Material of Construction Aluminum Cable Jacket Material PVC Cable Outer Diameter (OD) 4.5 +/- 0.15 mm	BATTERY		
LED Indicators White (Connection) PHYSICAL Silver Color Silver Material of Construction Aluminum Cable Jacket Material PVC Cable Outer Diameter (OD) 4.5 +/- 0.15 mm	Battery Charging (5V/1.5A Port)	No	
LED Indicators White (Connection) PHYSICAL Silver Color Silver Material of Construction Aluminum Cable Jacket Material PVC Cable Outer Diameter (OD) 4.5 +/- 0.15 mm	USER INTERFACE, ALERTS & CONTROLS		
PHYSICAL Color Silver Material of Construction Aluminum Cable Jacket Material PVC Cable Outer Diameter (OD) 4.5 +/- 0.15 mm	LED Indicators		
Material of Construction Aluminum Cable Jacket Material PVC Cable Outer Diameter (OD) 4.5 +/- 0.15 mm	PHYSICAL		
Cable Jacket Material PVC Cable Outer Diameter (OD) 4.5 +/- 0.15 mm	Color	Silver	
Cable Outer Diameter (OD) 4.5 +/- 0.15 mm	Material of Construction	Aluminum	
	Cable Jacket Material	PVC	
Wire Gauge (AWG) 24/30	Cable Outer Diameter (OD)	4.5 +/- 0.15 mm	
	Wire Gauge (AWG)	24/30	

TRIPP-LITE

Housing Color	Silver	
Included Mounting Accessories	No	
Unit Dimensions (hwd / in.)	0.530 x 1.310 x 4.470	
Unit Packaging Type	Box	
Unit Weight (Ibs.)	0.154	
Unit Weight (kg)	0.07	
ENVIRONMENTAL		
Operating Temperature Range	32 to 104 F (0 to 40 C)	
Storage Temperature Range	-14 to 140 F (-10 to 60 C)	
Relative Humidity	0 ~ 90% RH	
CONNECTIONS		
Number of Ports	5	
Side A - Connector 1	USB C (MALE)	
Side B - Connector 1	(2) USB 3.0 A (FEMALE)	
Side B - Connector 2	MICRO SD (FEMALE)	
Side B - Connector 3	SD (FEMALE)	
Side B - Connector 4	USB C (FEMALE)	
FEATURES & SPECIFICATIONS		
Data Transfer Rate	5 Gbps	
USB Hub Ports	Yes	
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)	
Driver Required	No	
SD Card Specification	Micro SD; SD	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	3-year limited warranty	



1000 Eaton Boulevard Cleveland, OH 44122 United States



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.