



RoHS COMPLIANT

- NOTES:
1. MATERIAL: PA66 GF30% PER P/N 899921251  
REGRIND RATIO AS PER DATA SHEET
  2. ALLOWABLE FLASH 0.08 UNLESS OTHERWISE SPECIFIED.
  3. REFER TO 3D CAD MODEL (EM-36783-015) FOR DIMENSIONS NOT SHOWN ON THIS DRAWING.
  4. TSC DENOTES THEORETICAL SHARP CORNER.

<b>ENTER DESCRIPTION</b> EC NO: I2013-0160 DRAWN: MR/MAKRI SHINA 2013/04/22 CHKD: CHIKO APPR: KPRASAD 2013/05/02 REV:	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
	▽=0	4 PLACES ± --- ± ---	MM ONLY	10:1	METRIC	CAVITY PLUG 1.2MM SEALED CONNECTOR SYSTEM <b>molex</b>
	▽=0	3 PLACES ± 0.005 ± ---	DRAWN BY	DATE	TITLE	
	▽=0	2 PLACES ± 0.13 ± ---	TMPAT I L	2011/12/07		
▽=0	1 PLACE ± 0.25 ± ---	CHECKED BY	DATE			
	0 PLACE ± ±	0 PLACE ± ±	APPROVED BY	DATE		
		ANGULAR ± 1/2°	KPRASAD	2011/12/07		
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	MATERIAL NO.	DOCUMENT NO.		
			367830015	SD-36783-013		
			SIZE A2	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		