

## 20.33 10.67 0 $\bigcirc$ Ō 0 0

## NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATED

**OPERATING TEMPERATURE:** 


.X ±0.25 .XX ±0.13

.XXX ±0.05

POWER/CO-AX CONTACT RATING: 30A (CURRENT) (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX.

**INSULATOR RESISTANCE:** DIELECTRIC WITHSTANDING VOLTAGE: 5000MΩ min.

1000V AC rms



|  | COMBINATION D-SUB  |  | SW REFERENCE NO.: 630 COMBO ASSEMBLY |                  |       |
|--|--|--|--------------------------------------|------------------|-------|
|  |  |  | DRAWN: C.B                           | DATE: JAN. 01/20 | 19    |
|  |  |  | CHECKED:                             | DATE:            |       |
|  | EDAC INC<br>TORONTO, ONTARIO<br>CANADA<br>YOUR CONNECTION TO QUALITY & SERVICE | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND<br>SHALL NOT BE REPRODUCED,OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1)               | SHEET 1 OF       | 2     |
|  |  |  | DRAWING NUMBER: 630-5W5-250-3NC      |                  | ISSUE |
|  |  |  | PART NUMBER: 630-5W5                 | -250-3NC         | 1     |



COMPLIANT

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



-55°C ~ 125°C

