Ξ	۵		п		т		D		C		Φ	Þ		
		V Thread												
ى									LAYO	UT SHOWN AS E	EXAMPLE			3
			Keying Show	vn as example										
CHARACTERISTICS					tor dimension	1								
-Standard : Based or	MIL-DTL-38999 Series III			Dim ØS	Nominal 35.7 Max									
-Shell Material -Shell Plating -Insulator -Contacts -Seals & Grommet	: Composite : Without Plating : Thermoplastic : Copper Alloy : Silicon Elastomer			Z VV THREAD	31 Max M25x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)							
-Contact Plating	: Gold over copper Alloy	ν 0.8μm minimum								Count FR		n & Control List ot Listed		2
-Durability -Delivered without S									PN	: 8D517X	(06PNL			
-Temperature Range -Salt Spray	-65°C to +175°C : 2000 hours						A 18-1	10-2016 Fir	st Release					
	: 21.9 g ± 10%								Latest modification	- by			MOD N°	_
							Designed By:		Date:			ISTOMER DRAWING		-
							TITL	LE		Compo	osite Plug 8D s	eries		
BASIC SERIES:	8D 5 vith RFI Shielding	- 17 X	06 P N	L	Delivered W/	O Contacts	SCALE NA	E	$] \bigoplus$	General linear Tolerances: ±		NPRDS / PROJECT <b>859</b>		
CONTACT TYPE : S SHELL SIZE : 17	tandard Crimp Contact				ORIEN CONTACT TYPE : PIN(50	TATION : N 00 Matings)	SOUR	RIAU	WWW.S	OURIAU.(	СОМ	This document is the pro SOURIAU it must not be reprodu communicated without p	ced or	
PLATING : X =	Without Plating				CONTACT LAYC		FORMAT			SOURIAU	UDRG N°	· · · · · · · · · · · · · · · · · · ·	SHEET	-
			I				A3			8D517X0			1/2	
											-		1	

r	I	۵	וד	m		0	
		Contact Layout					
4		$ \begin{array}{c} \bullet^{+Y} \\ \hline \\ E \\ \oplus \end{array} \begin{array}{c} A \\ \oplus \\ \hline \\ D \\ \oplus \end{array} \begin{array}{c} F \\ \oplus \end{array} \begin{array}{c} \Phi \\ \oplus \end{array} \end{array} \right) + x $					
_	-X -	Contacts (Insert arrangement 17-6)					
ω	size no. cor	(mm)  (mm)    +.121 (3.07)  +.209 (5.31)    +.241 (6.12)  +.000 (0.00)    +.000 (0.00) 241 (6.12)   241 (6.12)  +.000 (0.00)   121 (3.07)  +.209 (5.31)					
			-			SOURIAU shall not be liab due to a use of the Pro the Specifications issued by	oducts w
N						(professional recor PN: 8D	Count FR
					A 18-10-20 ISS DATE Designed By:	116 First Release	
					TITLE SCALE NA	Genera Toler	Compo al linear rances: ±
					FORMAT		
		<u>^</u>	F	r (	A3		517X(
	Н	G		E	D	C	I

				4			
				3			
any non-conformity or damage which does not comply with r of the Parties or by a third party dation, technical notice.)							
ntry R	R Not Listed						
	6PNL						
		CUSTOMER DRAWING	MOD N°				
posite Plug 8D series							
r		NPRDS / PROJECT					
		859					
.cc	M	perty of ed or rmission					
U	DRG N°		SHEET				
<u>(0</u> 6	06PNL-C 2/2						
	В	A		-			