






## Heyco® -Tite Aluminum Liquid Tight Cordgrips Straight-Thru, NPT Hubs

*The Ultimate in Liquid Tight Strain Relief Protection*

- **Aluminum construction** provides excellent durability and performance for most **industrial applications**.
- For use in both indoor and outdoor applications to prevent cable pull-out, control arc of bend, and to provide a tight seal against environmental elements such as dirt, moisture, and coolants.
- IP 67 rated.
- Protect cable from damage and pull-out and are used in conduit hubs or knock-outs at the point where the electrical cable is to be terminated.
- Unique design with a combination tightening surface that includes both a hex area and a knurled surface.
- Anti-friction washer allows for easier compression.
- DFARS Compliant

CABLE DIA. RANGE				PART NO. Machined Aluminum	THREAD SIZE	UL	PART DIMENSIONS							
Minimum		Maximum					A Clearance Hole Dia.		B Max. O.A. Length		C Thread Length		D Wrenching Flat Size	
in.	mm.	in.	mm.				in.	mm.	in.	mm.	in.	mm.	in.	mm.
.125	3,2	.188	4,8	<b>M5000*</b>	NPT 1/4	UL	.54	13,7	1.38	35,1	.44	11,2	.88	22,4
.188	4,8	.250	6,4	<b>M5001</b>										
.250	6,4	.312	7,9	<b>M5002</b>										
.312	7,9	.375	9,5	<b>M5003</b>										
.125	3,2	.188	4,8	<b>M5005*</b>	NPT 3/8	UL	.68	17,3	1.38	35,1	.44	11,2	.88	22,4
.188	4,8	.250	6,4	<b>M5006</b>										
.250	6,4	.312	7,9	<b>M5007</b>										
.312	7,9	.375	9,5	<b>M5008</b>										
.125	3,2	.188	4,8	<b>M5010*</b>	NPT 1/2	UL	.88	22,4	1.38	35,1	.44	11,2	.88	22,4
.188	4,8	.250	6,4	<b>M5011</b>										
.250	6,4	.312	7,9	<b>M5012</b>										
.312	7,9	.375	9,5	<b>M5013</b>										
.375	9,5	.438	11,1	<b>M5014</b>										
.125	3,2	.188	4,8	<b>M5015*</b>	NPT 1/2	UL	.88	22,4	1.62	41,1	.56	14,2	1.13	28,7
.188	4,8	.250	6,4	<b>M5016</b>										
.250	6,4	.312	7,9	<b>M5017</b>										
.312	7,9	.375	9,5	<b>M5018</b>										
.375	9,5	.438	11,1	<b>M5019</b>										
.438	11,1	.500	12,7	<b>M5020</b>										
.500	12,7	.562	14,3	<b>M5021</b>										
.562	14,3	.625	15,9	<b>M5022</b>										

Assembled O-ring **INCLUDED**. \*Not UL Listed or CSA Certified.  
Locknut not included - See page 3-48 for Metal Locknuts.



**SUGGESTED CLEARANCE HOLE FOR NONTHEADED MOUNTING**

*Quick Specs*

Material  
Certifications

Flammability Rating  
Temperature Range  
IP Rating

Aluminum with Neoprene Sealing Gland and Viton® O-Ring  
UL Listed under Underwriters' Laboratories File E51579  
CSA Certified by Canadian Standard Association File 258093

94V-2  
-40°F (-40°C) to 250°F (121°C)  
IP 67