


TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.











 .X
 ±0.25

 .XX
 ±0.13

 .XXX
 ±0.05

NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

OPERATING TEMPERATURE:

POWER/CO-AX CONTACT RATING:30A (CURRENT)(IF PRESENT)SIGNAL CONTACT CURRENT RATING:5A PER CONTACTSIGNAL CONTACT RESISTANCE:10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 5000MΩ min.


1000V AC rms

STEEL, TIN PLATED

-55°C ~ 125°C

THERMOPLASTIC POLYESTER, UL94V-0

COPPER ALLOY, 30µ" GOLD PLATED



	COMBINATION D-SUB			SW REFERENCE NO.: 629 COMBO ASSEMBLY						
COMBI				DRAWN: C.B			DATE: JAN. 01/2019			
				CHECKED:		DATE:				
EDAC	EDAC INC TORONTO, ONTARIO CANADA	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS	SCALE:	(IN C.A.D. 1:	1)	SHEET	1	OF	2	
			DRAWING NUMBER: 629-11W1			1650-3T6			ISSUE	
YOUR CONNECTION TO QUALITY &	YOUR CONNECTION TO QUALITY & SERVICE		PART NUM	MBER:	629-11W1	1650-3T6	;		1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

