



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Black Zinc Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +175°C
- Salt Spray : 500 hours
- Mass : 11.73 g ± 10%

| Connector dimension |               |
|---------------------|---------------|
| Dim                 | Nominal       |
| P                   | 3.25±0.2      |
| PP                  | 4.93±0.2      |
| R1                  | 20.62         |
| R2                  | 18.26         |
| S                   | 26.2±0.3      |
| V                   | 20.83+0/-1.25 |
| W                   | 2.1/2.5       |
| Z                   | 31.5 Max      |
| VV THREAD           | M15x1-6g      |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

|         |                             |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR      | Not Listed                  |

**PN: 8D011Z98AE**

|                |                                       |                                |   |
|----------------|---------------------------------------|--------------------------------|---|
| A              | 09-10-2016                            | First Release                  |   |
| ISS            | DATE                                  | Latest modification - by       | MOD N°  |
| Designed By:   |                                       | Date:                          | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Aluminium Receptacle 8D series</b> |                                |   |
| SCALE          | NA                                    | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>   |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                |                                | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>A3</b>                             |                                | <b>SOURIAU DRG N° 8D011Z98AE-C</b>  |
|                |                                       |                                | SHEET<br>1/2  |

BASIC SERIES: 8D 0 - 11 Z 98 A E

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

SHELL SIZE : 11

PLATING : Z = Black Zinc Nickel

ORIENTATION : E

CONTACT TYPE : PIN(500 Matings)

CONTACT LAYOUT : 11-98

Contact Layout



| Contacts<br>(Insert arrangement 11-98) |                  |             |
|--|------------------|-------------|
| Contact position ID                    | Contact location |             |
|  | X-axis (mm)      | Y-axis (mm) |
| A                                      | +000 (0.00)      | +130 (3.30) |
| B                                      | +130 (3.30)      | +000 (0.00) |
| C                                      | +065 (1.65)      | -113 (2.87) |
| D                                      | -065 (1.65)      | -113 (2.87) |
| E                                      | -130 (3.30)      | +000 (0.00) |
| F                                      | +000 (0.00)      | +000 (0.00) |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 11         | -98             | 6                  | 20            | I              | All              | MS20050-98 |

Panel Cutout



| Dim | Nominal    |
|-----|------------|
| ØA  | 20.22 min  |
| ØAA | 15.88 min  |
| R1  | 20.62      |
| ØT  | 3.25 ±0.13 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D011Z98AE

|                |                                |                                |   |
|----------------|--------------------------------|--------------------------------|---|
| A              | 09-10-2016                     | First Release                  |   |
| ISS            | DATE                           | Latest modification - by       | MOD N°  |
| Designed By:   |                                | Date:                          | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | Aluminium Receptacle 8D series |                                |   |
| SCALE          | NA                             | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>   |
| <b>SOURIAU</b> | WWW.SOURIAU.COM                |                                | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | A3                             |                                | SOURIAU DRG N°<br>8D011Z98AE-C  |
|                |                                |                                | SHEET<br>2/2  |