


## VP3225K401R130

VP, Varistors, Plastic Encapsulated, 170 V, 130 VAC, 205 V, 340 V, 5 A, 400 A, 7 J, 100 mW  $\,$ 



General Information	
Series	VP
Туре	Varistors
Style	SMD Molded
Description	Surface Mount Varistors
Features	Plastic Encapsulated
Termination	Nickel Tin
RoHS	Yes
Qualifications	UL
AEC-Q200	No

Click here for the 3D model.

Dimensions	
Chip Size	3225
L	8mm +/-0.5mm
W	6.3mm +/-0.4mm
Н	3.4mm +/-0.3mm
F	3mm +/-0.3mm
В	1.5mm +/-0.3mm
K	1.7mm +/-0.3mm

Dimensions	
Chip Size	3225
L	8mm +/-0.5mm
W	6.3mm +/-0.4mm
Н	3.4mm +/-0.3mm
F	3mm +/-0.3mm
В	1.5mm +/-0.3mm
K	1.7mm +/-0.3mm

Specifications	
Voltage DC	170 VDC (25C)
Voltage AC	130 VAC
Temperature Range	-40/+85°C
Storage Temperature Range	-40/+125°C
Varistor Voltage	205 VDC at 1 mA
Clamping Voltage	340 V
Clamping Current	5 A (8/20 us MAX)
Surge Current	400 A (8/20 us MAX)
Energy	7 J (10/1000 us MAX)
Capacitance	160 pf (1kHz)

	1
Packaging T8	kR
Packaging Quantity 15	00

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.