ſ	т Q т.		0	₿ >		7
4	Z PEQUIT N PEQUIT N PEQ					4
ω						3
			LAYOUT SHOWN AS EXA	MPLE		
	Keying Shown as example					
	CHARACTERISTICS Connector dimension					
-	-Standard : Based on MIL-DTL-38999 Series III ØS 48 Max					
	-Shell Material : Aluminium -Shell Plating : Nickel VV THREAD M37x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with			
	Shell Plating : Nickel VV THREAD M37x1-6g Insulator : Thermoplastic		the Specifications issued by either of the Parties or by a third party			
	-Contacts : Copper Alloy		(professional recommendation	n, technical notice.)		
	-Seals & Grommet : Silicon Elastomer		Country	Iurisdiction & Control List	J ¬	
N	-Contact Plating : Gold over copper Alloy 0.8µm minimum		CountryJurisdiction & Control ListFRNot Listed			2
	-Durability : 500 Mating cycles					
	-Delivered with Souriau contacts and Accessories		PN: 8D525F61BN			
	-Temperature Range - 65°C to +200°C					_
	-Salt Spray : 48 hours	A 06-10-20	16 First Release			
	-Mass : 81.42 g ± 10%	ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	_
						_
		TITLE	Aluminiu	ım Plug 8D series		
	BASIC SERIES: 8D 5 - 25 F 61 B N	SCALE	General linear Tolerances:	NPRDS / PROJECT 859		
<u>→</u>	SHELL TYPE : Plug with RFI Shielding	NA		This document is the pro	perty of	_ 1
	CONTACT TYPE : Standard Crimp Contact ORIENTATION : N		SOURIAU WWW.SOURIAU.COM it must not be reproduced or			
	HELL SIZE : 25 CONTACT TYPE : SOCKET(500 Matings)			communicated without pe		
	PLATING : F = Nickel CONTACT LAYOU		SOURIAU E	DRG N°	SHEET	
		A3	8D525F61	LBN-C	1/2	
	H G F E	D	С	BA	1	_

