

## N-Channel Enhancement Mode Power MOSFET

<p><b>Description</b></p> <p>The GT060N04D5 uses advanced trench technology to provide excellent <math>R_{DS(ON)}</math>, low gate charge. It can be used in a wide variety of applications.</p> <p><b>General Features</b></p> <ul style="list-style-type: none"> <li>● <math>V_{DS}</math> 40V</li> <li>● <math>I_D</math> (at <math>V_{GS} = 10V</math>) 62A</li> <li>● <math>R_{DS(ON)}</math> (at <math>V_{GS} = 10V</math>) &lt; 5.5mΩ</li> <li>● <math>R_{DS(ON)}</math> (at <math>V_{GS} = 4.5V</math>) &lt; 7.5mΩ</li> <li>● 100% Avalanche Tested</li> <li>● RoHS Compliant</li> </ul> <p><b>Application</b></p> <ul style="list-style-type: none"> <li>● Power switch</li> <li>● DC/DC converters</li> </ul>	<p>Schematic diagram</p> <p>pin assignment</p> <p>DFN5x6-8L</p>
---	---

Ordering Information			
Device	Package	Marking	Packaging
GT060N04D5	DFN5x6-8L	GT060N04	5000pcs/Reel

Absolute Maximum Ratings $T_C = 25^\circ C$ , unless otherwise noted			
Parameter	Symbol	Value	Unit
Drain-Source Voltage	$V_{DS}$	40	V
Continuous Drain Current	$I_D$	62	A
Pulsed Drain Current (note1)	$I_{DM}$	248	A
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Power Dissipation	$P_D$	39	W
Single pulse avalanche energy (note2)	$E_{AS}$	56	mJ
Operating Junction and Storage Temperature Range	$T_J, T_{stg}$	-55 To 150	°C

Thermal Resistance			
Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Ambient	$R_{thJA}$	64	°C/W
Maximum Junction-to-Case	$R_{thJC}$	3.2	°C/W

**Specifications**  $T_J = 25^\circ\text{C}$ , unless otherwise noted

Parameter	Symbol	Test Conditions	Value			Unit
			Min.	Typ.	Max.	
<b>Static Parameters</b>						
Drain-Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{\text{GS}} = 0\text{V}, I_D = 250\mu\text{A}$	40	--	--	V
Zero Gate Voltage Drain Current	$I_{\text{DSS}}$	$V_{\text{DS}} = 40\text{V}, V_{\text{GS}} = 0\text{V}$	--	--	1	$\mu\text{A}$
Gate-Source Leakage	$I_{\text{GSS}}$	$V_{\text{GS}} = \pm 20\text{V}$	--	--	$\pm 100$	nA
Gate-Source Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}} = V_{\text{GS}}, I_D = 250\mu\text{A}$	1	1.4	2.3	V
Drain-Source On-Resistance	$R_{\text{DS}(\text{on})}$	$V_{\text{GS}} = 10\text{V}, I_D = 30\text{A}$	--	4.5	5.5	$\text{m}\Omega$
		$V_{\text{GS}} = 4.5\text{V}, I_D = 20\text{A}$	--	6	7.5	
Forward Transconductance	$g_{\text{FS}}$	$V_{\text{GS}} = 5\text{V}, I_D = 30\text{A}$	--	54	--	S
<b>Dynamic Parameters</b>						
Input Capacitance	$C_{\text{iss}}$	$V_{\text{GS}} = 0\text{V}, V_{\text{DS}} = 20\text{V}, f = 1.0\text{MHz}$	--	1276	--	$\text{pF}$
Output Capacitance	$C_{\text{oss}}$		--	663	--	
Reverse Transfer Capacitance	$C_{\text{rss}}$		--	36	--	
Total Gate Charge	$Q_g$	$V_{\text{DD}} = 20\text{V}, I_D = 30\text{A}, V_{\text{GS}} = 10\text{V}$	--	44	--	$\text{nC}$
Gate-Source Charge	$Q_{\text{gs}}$		--	7.5	--	
Gate-Drain Charge	$Q_{\text{gd}}$		--	7	--	
Turn-on Delay Time	$t_{\text{d}(\text{on})}$	$V_{\text{DD}} = 20\text{V}, I_D = 30\text{A}, R_G = 1.6\Omega$	--	9	--	$\text{ns}$
Turn-on Rise Time	$t_r$		--	3.5	--	
Turn-off Delay Time	$t_{\text{d}(\text{off})}$		--	30	--	
Turn-off Fall Time	$t_f$		--	4	--	
<b>Drain-Source Body Diode Characteristics</b>						
Continuous Body Diode Current	$I_S$	$T_C = 25^\circ\text{C}$	--	--	62	A
Body Diode Voltage	$V_{\text{SD}}$	$T_J = 25^\circ\text{C}, I_{\text{SD}} = 30\text{A}, V_{\text{GS}} = 0\text{V}$	--	--	1.2	V
Reverse Recovery Charge	$Q_{\text{rr}}$	$I_F = 30\text{A}, V_{\text{GS}} = 0\text{V}$ $dI/dt = 100\text{A}/\mu\text{s}$	--	60	--	$\text{nC}$
Reverse Recovery Time	$T_{\text{rr}}$		--	21	--	ns

**Notes**

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2. EAS condition :  $T_J=25^\circ\text{C}$ ,  $V_{\text{DD}}=40\text{V}$ ,  $V_{\text{GS}}=10\text{V}$ ,  $L=0.5\text{mH}$ ,  $R_G=25\Omega$
3. Identical low side and high side switch with identical  $R_G$


### Gate Charge Test Circuit



### Switch Time Test Circuit




### EAS Test Circuit




**Typical Characteristics**  $T_J = 25^\circ\text{C}$ , unless otherwise noted


**Figure 1. Output Characteristics**




**Figure 2. Transfer Characteristics**




**Figure 3. Drain Source On Resistance**




**Figure 4. Gate Charge**



**Figure 5. Capacitance**




**Figure 6. Source-Drain Diode Forward**




**Typical Characteristics**  $T_J = 25^\circ\text{C}$ , unless otherwise noted


**Figure 7. Drain-Source On-Resistance**




**Figure 8. Safe Operation Area**



**Figure 9. Normalized Maximum Transient Thermal Impedance**



## DFN5X6-8L Package information



SYMBOL	COMMON			
	MM		INCH	
	MIN	MAX	MIN	MAX
A	1.03	1.17	0.0406	0.0461
b	0.34	0.48	0.0134	0.0189
c	0.824	0.970	0.0324	0.0382
D	4.80	5.40	0.1890	0.2126
D1	4.11	4.31	0.1618	0.1697
D2	4.80	5.00	0.1890	0.1969
E	5.59	6.15	0.2343	0.2421
E1	5.65	5.85	0.2224	0.2303
E2	1.60	-	0.0630	-
e	1.27	BSC	0.05	BSC
L	0.05	0.25	0.0020	0.0098
L1	0.38	0.50	0.0150	0.0197
L2	0.38	0.50	0.0150	0.0197
H	3.30	3.50	0.1299	0.1378
I	-	0.18	-	0.0070